



US009167097B2

(12) **United States Patent**
Kung et al.

(10) **Patent No.:** **US 9,167,097 B2**
(45) **Date of Patent:** **Oct. 20, 2015**

(54) **RESPONDING TO A CALL WITH A PROMPT
AND ROUTING THE CALL TO A PHONE
SELECTED IN RESPONSE TO THE PROMPT**

H04M 7/0066 (2013.01); *H04L 29/12066*
(2013.01); *H04L 61/1511* (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **Shoretel, Inc.**, Sunnyvale, CA (US)

(72) Inventors: **Fen-Chung Kung**, Bridgewater, NJ
(US); **Anish Sankalia**, Iselin, NJ (US);
Spencer C. Wang, Parsippany, NJ (US);
Jesse E. Russell, Piscataway, NJ (US)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,694,487 A 9/1987 Chang et al.
4,887,152 A 12/1989 Matsuzaki et al.

(Continued)

(73) Assignee: **Shoretel, Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 124 days.

FOREIGN PATENT DOCUMENTS

AU 59680/98 9/1998
CA 2134132 10/1994

(Continued)

(21) Appl. No.: **13/944,600**

(22) Filed: **Jul. 17, 2013**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2013/0308498 A1 Nov. 21, 2013

Office Action dated Mar. 9, 2012 in U.S. Appl. No. 12/481,250,
USPTO-Pair, 8 pages.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 12/481,250, filed on
Jun. 9, 2009, now Pat. No. 8,514,846, which is a
continuation of application No. 11/649,054, filed on
Jan. 3, 2007, now Pat. No. 7,564,839, which is a
continuation of application No. 09/475,206, filed on
Dec. 30, 1999, now Pat. No. 7,180,889.

Primary Examiner — Otis L Thompson, Jr.

(74) *Attorney, Agent, or Firm* — Omkar K. Suryadevara;
Silicon Valley Patent Group LLP

(57)

ABSTRACT

A method and apparatus provide multiple telephone lines
using a single directory number. A method and apparatus
associate multiple directory numbers with multiple telephone
lines. A broadband residential gateway (BRG) is a user inter-
face to a broadband communication system providing pack-
etized telephone service and other media services. The BRG
can provide greeting and message features. A greeting may
instruct a caller to select a name or extension which is asso-
ciated with a party the caller is attempting to reach. Also, a
message, played after the greeting, may further instruct the
caller.

20 Claims, 9 Drawing Sheets

(51) **Int. Cl.**

H04L 12/66 (2006.01)

H04M 3/54 (2006.01)


H04L 29/06 (2006.01)

H04M 7/00 (2006.01)

H04L 29/12 (2006.01)

(52) **U.S. Cl.**

CPC *H04M 3/543* (2013.01); *H04L 29/06027*
(2013.01); *H04L 65/1026* (2013.01); *H04L*
65/1036 (2013.01); *H04L 65/1069* (2013.01);



(56)

References Cited

U.S. PATENT DOCUMENTS

4,922,529	A	5/1990	Kiel	5,862,134	A	1/1999	Deng
4,926,462	A	5/1990	Ladd et al.	5,864,612	A	1/1999	Strauss et al.
4,995,074	A	2/1991	Goldman et al.	5,867,495	A	2/1999	Elliott et al.
5,099,509	A	3/1992	Morganstein et al.	5,870,565	A	2/1999	Glitho
5,253,341	A	10/1993	Rozmanith et al.	5,881,142	A	3/1999	Frankel et al.
5,268,958	A	12/1993	Nkano	5,887,259	A	3/1999	Zicker et al.
5,274,700	A	12/1993	Gechter et al.	5,889,844	A	3/1999	Kim et al.
5,276,731	A	1/1994	Arbel et al.	5,894,504	A	4/1999	Alfred et al.
5,278,894	A	1/1994	Shaw	5,896,444	A	4/1999	Perlman et al.
5,341,425	A	8/1994	Wasilewski et al.	5,898,668	A	4/1999	Shaffer
5,349,638	A	9/1994	Pitroda et al.	5,905,776	A	5/1999	Shaffer
5,363,431	A	11/1994	Schull et al.	5,907,604	A	5/1999	Hsu
5,375,161	A	12/1994	Fuller et al.	5,912,962	A	6/1999	Bosco
5,400,327	A	3/1995	Dezonno	5,916,302	A	6/1999	Dunn et al.
5,416,842	A	5/1995	Aziz	5,917,624	A	6/1999	Wagner
5,428,608	A	6/1995	Freeman et al.	5,920,705	A	7/1999	Lyon et al.
5,440,616	A	8/1995	Harrington et al.	5,923,731	A	7/1999	McClure
5,449,970	A	9/1995	Kumar et al.	5,933,490	A	8/1999	White et al.
5,471,523	A	11/1995	Smith et al.	5,937,347	A	8/1999	Gordon
5,479,411	A	12/1995	Klein	5,940,598	A	8/1999	Strauss et al.
5,483,588	A	1/1996	Eaton et al.	5,943,397	A	8/1999	Gabin et al.
5,533,100	A	7/1996	Bass et al.	5,946,381	A	8/1999	Danne et al.
5,533,110	A	7/1996	Pinard et al.	5,946,386	A	8/1999	Rogers et al.
5,533,111	A	7/1996	Schlanger	5,956,717	A	9/1999	Kraay et al.
5,537,157	A	7/1996	Washino et al.	5,970,072	A	10/1999	Gammethaler, Jr. et al.
5,546,447	A	8/1996	Skarbo et al.	5,974,142	A	10/1999	Heer et al.
5,583,929	A	12/1996	Ardon	5,978,451	A	11/1999	Swan et al.
5,590,184	A	12/1996	London	5,978,470	A	11/1999	Shaffer et al.
5,592,529	A	1/1997	Linsker	5,982,774	A	11/1999	Foladare et al.
5,600,643	A	2/1997	Robrack, II	5,987,508	A	11/1999	Agraharam et al.
5,610,910	A	3/1997	Focsaneanu et al.	5,999,525	A	12/1999	Krishnaswamy et al.
5,612,997	A	3/1997	Vallelonga, Sr. et al.	5,999,602	A	12/1999	Yang et al.
5,615,252	A	3/1997	Sizer, II et al.	5,999,612	A	12/1999	Dunn et al.
5,615,257	A	3/1997	Pezzullo et al.	6,005,602	A	12/1999	Matthews, III
5,629,978	A	5/1997	Blumhardt et al.	6,005,845	A	12/1999	Svennesson et al.
5,652,789	A	7/1997	Miner et al.	6,006,253	A	12/1999	Kumar et al.
5,657,426	A	8/1997	Waters et al.	6,009,177	A	12/1999	Sudia
5,657,446	A	8/1997	Pinard et al.	6,011,909	A	1/2000	Newlin et al.
5,689,555	A	11/1997	Sonnenberg	6,014,379	A	1/2000	White et al.
5,689,708	A	11/1997	Regnier et al.	6,023,724	A	2/2000	Bhatia et al.
5,696,815	A	12/1997	Smyk	6,028,848	A	2/2000	Bhatia et al.
5,706,342	A	1/1998	Baeder et al.	6,031,896	A	2/2000	Gardell et al.
5,708,961	A	1/1998	Hylton et al.	6,044,349	A	3/2000	Tolopka et al.
5,712,903	A	1/1998	Bartholomew et al.	6,052,444	A	4/2000	Ferry et al.
5,712,907	A	1/1998	Wegner et al.	6,052,725	A	4/2000	McCann et al.
5,719,872	A	2/1998	Dubberly et al.	6,061,434	A	5/2000	Corbett
5,724,411	A	3/1998	Eisdorfer et al.	6,078,582	A	6/2000	Curry et al.
5,724,412	A	3/1998	Srinivasan	6,084,892	A	7/2000	Benash et al.
5,740,230	A	4/1998	Vaudreuil	6,094,431	A	7/2000	Yamato et al.
5,740,231	A	4/1998	Cohn et al.	6,104,800	A	8/2000	Benson
5,742,596	A	4/1998	Baratz et al.	6,108,330	A	8/2000	Bhatia et al.
5,742,905	A	4/1998	Pepe et al.	6,115,393	A	9/2000	Engel et al.
5,745,553	A	4/1998	Mirville et al.	6,118,432	A	9/2000	Kotorov et al.
5,751,706	A	5/1998	Land et al.	6,118,768	A	9/2000	Bhatia et al.
5,751,760	A	5/1998	Fuller et al.	6,122,357	A	9/2000	Farris et al.
5,761,306	A	6/1998	Lewis	6,128,304	A	10/2000	Gardell et al.
5,764,752	A	6/1998	Waite et al.	6,137,870	A	10/2000	Scherer
5,768,389	A	6/1998	Ishii	6,144,401	A	11/2000	Casemant et al.
5,768,513	A	6/1998	Kuthyar et al.	6,148,193	A	11/2000	Miska et al.
5,784,444	A	7/1998	Snyder et al.	6,154,465	A	11/2000	Pickett
5,793,413	A	8/1998	Hylton et al.	6,154,531	A	11/2000	Clapper
5,796,394	A	8/1998	Wicks et al.	6,157,708	A	12/2000	Gordon
5,796,424	A	8/1998	Ely et al.	6,160,880	A	12/2000	Allen
5,796,952	A	8/1998	Davis et al.	6,163,531	A	12/2000	Kumar
5,805,587	A	9/1998	Norris et al.	6,169,795	B1	1/2001	Dunn et al.
5,809,126	A	9/1998	Smith et al.	6,188,760	B1	2/2001	Oran et al.
5,809,128	A	9/1998	McMullin	6,192,116	B1	2/2001	Mayak
5,809,520	A	9/1998	Edwards et al.	6,215,858	B1	4/2001	Bartholomew et al.
5,814,798	A	9/1998	Zancho	6,219,045	B1	4/2001	Leahy et al.
5,822,415	A	10/1998	Gordon	6,226,358	B1	5/2001	Schwartz et al.
5,825,829	A	10/1998	Borazjani et al.	6,229,887	B1	5/2001	Albers et al.
5,825,862	A	10/1998	Voit et al.	6,233,235	B1	5/2001	Burke et al.
5,841,839	A	11/1998	Fogg et al.	6,233,313	B1	5/2001	Farris et al.
5,850,429	A	12/1998	Joyce et al.	6,233,318	B1	5/2001	Picard et al.
5,859,902	A	1/1999	Freedman	6,236,653	B1	5/2001	Dalton et al.
				6,253,249	B1	6/2001	Belzile
				6,259,449	B1	7/2001	Saxena et al.
				6,262,979	B1	7/2001	Anderson et al.
				6,263,065	B1	7/2001	Durinovic-Johri et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

6,263,503	B1	7/2001	Margulis	
6,266,405	B1	7/2001	Madour et al.	
6,285,750	B1	9/2001	Brachman et al.	
6,289,025	B1	9/2001	Pang et al.	
6,295,298	B1	9/2001	Hrastar et al.	
6,300,947	B1	10/2001	Kanevsky	
6,304,566	B1	10/2001	Schessel	
6,308,221	B1	10/2001	Perlman et al.	
6,324,279	B1	11/2001	Kalmanek, Jr. et al.	
6,330,244	B1	12/2001	Swartz et al.	
6,333,931	B1	12/2001	LaPier et al.	
6,345,047	B1	2/2002	Regnier	
6,351,464	B1	2/2002	Galvin et al.	
6,359,881	B1	3/2002	Gerszberg et al.	
6,374,296	B1	4/2002	Lim et al.	
6,385,305	B1	5/2002	Gerszberg et al.	
6,396,531	B1	5/2002	Gerszberg et al.	
6,397,080	B1	5/2002	Viktorsson et al.	
6,404,764	B1	6/2002	Jones et al.	
6,418,139	B1	7/2002	Akhtar	
6,418,216	B1	7/2002	Harrison et al.	
6,426,955	B1	7/2002	Gossett et al.	
6,430,276	B1	8/2002	Bouvier et al.	
6,438,222	B1	8/2002	Burg	
6,438,223	B1	8/2002	Eskafi et al.	
6,442,266	B1	8/2002	Wu	
6,445,922	B1	9/2002	Hiller et al.	
6,449,766	B1	9/2002	Fleming	
6,452,915	B1	9/2002	Jorgensen	
6,456,621	B1	9/2002	Wada et al.	
6,459,783	B1	10/2002	March et al.	
6,463,146	B1	10/2002	Hartley et al.	
6,466,570	B1	10/2002	Low et al.	
6,466,964	B1	10/2002	Leung et al.	
6,467,090	B1	10/2002	Brodigan	
6,473,858	B1	10/2002	Shimomura et al.	
6,490,274	B1	12/2002	Kim	
6,505,348	B1	1/2003	Knowles et al.	
6,519,249	B1	2/2003	Bennefeld et al.	
6,522,880	B1	2/2003	Verma et al.	
6,526,508	B2	2/2003	Akins, III et al.	
6,542,475	B1	4/2003	Bala et al.	
6,543,051	B1	4/2003	Manson et al.	
6,546,238	B1	4/2003	Nightingale et al.	
6,546,488	B2	4/2003	Dillon et al.	
6,560,203	B1	5/2003	Beser et al.	
6,560,216	B1	5/2003	McNiff et al.	
6,563,793	B1	5/2003	Golden et al.	
6,563,915	B1	5/2003	Salimando	
6,570,870	B1	5/2003	Berstis	
6,577,644	B1	6/2003	Chuah et al.	
6,584,096	B1	6/2003	Allan	
6,594,254	B1	7/2003	Kelly	
6,606,744	B1	8/2003	Mikurak	
6,611,531	B1	8/2003	Chen et al.	
6,633,635	B2	10/2003	Kung et al.	
6,654,607	B1	11/2003	Shobatake et al.	
6,690,663	B1	2/2004	Culver	
6,736,017	B2	5/2004	Mansky	
7,180,889	B1	2/2007	Kung et al.	
7,564,839	B1	7/2009	Kung et al.	
8,514,846	B2	8/2013	Kung et al.	
2001/0024436	A1 *	9/2001	Barracrough et al.	370/352
2001/0046237	A1 *	11/2001	Chan et al.	370/419
2002/0013941	A1	1/2002	Ward, III et al.	
2002/0101860	A1	8/2002	Thornton et al.	
2002/0124100	A1	9/2002	Adams	
2003/0095542	A1	5/2003	Chang et al.	

FOREIGN PATENT DOCUMENTS

EP	0794643	A2	9/1997
EP	0800325	A2	10/1997
EP	0758175	A1	12/1997

EP	0841831	A2	5/1998
EP	0845894	A2	6/1998
EP	0848560	A2	6/1998
EP	0856981	A2	8/1998
EP	0905959	A2	3/1999
EP	0921659	A1	6/1999
EP	0 928 095		7/1999
GB	2305090	A	3/1997
JP	06-334680		12/1994
JP	10-032643		2/1998
JP	10-070566		3/1998
JP	11-225169		8/1999
WO	WO 95/18501		7/1995
WO	WO 97/14238		4/1997
WO	WO 97/16007		5/1997
WO	WO 97/37483		10/1997
WO	WO 97/46073		12/1997
WO	WO 97/47118		12/1997
WO	WO 97/47119		12/1997
WO	WO 97/47127		12/1997
WO	WO 98/01985		1/1998
WO	WO 98/07266		2/1998
WO	WO 98/11704		3/1998
WO	WO 98/18269		4/1998
WO	WO 98/19240		5/1998
WO	WO 98/19448		5/1998
WO	WO 98/19471		5/1998
WO	WO 98/24224		6/1998
WO	WO 98/30002		7/1998
WO	WO 98/36551		8/1998
WO	WO 98/41032		9/1998
WO	WO 98/51057		11/1998
WO	WO 98/51063		11/1998
WO	WO 98/52332		11/1998
WO	WO 98/52339		11/1998
WO	WO 98/53617		11/1998
WO	WO 98/54871		12/1998
WO	WO 99/14924		3/1999
WO	WO 99/16201		4/1999
WO	WO 99/44352		9/1999
WO	WO 99/53719		10/1999
WO	WO 99/62242		12/1999

OTHER PUBLICATIONS

Amendment dated Jun. 11, 2012 in U.S. Appl. No. 12/481,250, USPTO-Pair, 11 pages.

Notice of Allowance dated Sep. 19, 2012 in U.S. Appl. No. 12/481,250, USPTO-Pair, 8 pages.

Amendment dated Dec. 16, 2012 in U.S. Appl. No. 12/481,250, USPTO-Pair, 13 pages.

Notice of Allowance dated Jan. 31, 2013 in U.S. Appl. No. 12/481,250, USPTO-Pair, 8 pages.

Amendment dated Apr. 4, 2013 in U.S. Appl. No. 12/481,250, USPTO-Pair, 11 pages.

Notice of Allowance dated Apr. 12, 2013 in U.S. Appl. No. 12/481,250, USPTO-Pair, 8 pages.

Summary of Examiner Interview dated Jul. 3, 2013 in U.S. Appl. No. 12/481,250, USPTO-Pair, 1 page.

Notice of Allowability dated Jul. 5, 2013 in U.S. Appl. No. 12/481,250, USPTO-Pair, 5 pages.

Doeringer W. et al. "Access architecture for a multiprotocol broadband backbone", Computer Networks and ISDN Systems 29 (1997), pp. 137-155, Elsevier Science B.V.;

Singh, R. K. et al. "A Programmable HIPPI Interface for a Graphics Supercomputer", ACM Special Interest Group on Computer Architecture, 1993, 0-8186-4340-4, pp. 124-132.;

Indiresan, A. et al. "The End: A Network Adapter Design Tool", Seventeenth Annual Joint Conference of Computer and Communications Societies, Proceedings, IEEE 0-7803-4383-2, 1998, pp. 756-764.;

Junkus, J. J. "Cable Telephony's Oxymoron", Communication Technology, Aug. 1999, pp. 24-26.;

Bass E. "IP Telephony: The Race Heats Up—Vendors, Start Your Engines", Communications Technology, Aug. 1999, pp. 48-50 & 52-55.;

(56)

References Cited**OTHER PUBLICATIONS**

Junkus, J. J. "SuperComm Highlights IP Telephony", Communication Technology, Aug. 1999, pp. 72, 74, 76, 78, 79;.

Dawson F. "Lighting a fire under IP telephony", CED, Oct. 1999, pp. 46-56;.

Komanecy M. "Solving IP Provisioning Challenges", CED, Oct. 1999, pp. 82-88;.

Shewmake B. "Microsoft teams With Nortel to offer Internet call waiting", Info World Media Group, Inc., Oct. 28, 1999, 1 page;.

Williams L. "IP-Ready Cable Telephony", Arris Interactive brochure, Nov. 1998, 4 sheets;.

H.323, Version 2.0, "A Primer on the H.323 Series Standard", DataBeam, May 15, 1998, pp. 1-16;.

"S-A Wins Thinnovation Award", Channel Surfing, Broadband Magazine, p. 28;.

Pease R. "ICI Contracts for Fiber-To-The-Curb Application", Lightwave, Nov., 1998, p. 27;.

Broadband Access Systems, Inc. website, Broadband Access Systems Inc. 1998;.

Samsung, "New Standard for Communications, Web Video Phone", brochure, Samsung Electronics, 1998;.

Antec, "Cornerstone: Picture Immediate Revenues for Your Network" brochure, Arris/Nortel Company;.

SmartWorks, "SmartWorks™ Call Agent", taken from 222.xvbridge.com/ca-detailed2.htm, printed Oct. 4, 1999;.

Low C. "The Internet Telephony Red Herring", Hewlett Packard, Article, 1996, pp. 1-15;.

Harris S. et al. "Intelligent Network Realization and Evolution: CCITT Capability Set 1 and Beyond," International Switching Symposium, Yokohama, Japan, Diversification and Integration of Networks and Switching Technologies Towards the 21st Century, Oct. 25-30, 1992, Proceedings vol. 2, pp. 127-131;.

IBM Technical Disclosure Bulletin, "Workstation Communications System", vol. 37, No. 9, Sep. 1994, pp. 101-104;.

Yang C. "Memo, Internet RFC/STD/FYI/BCP Archives, RFC1789, "INETPhone: Telephone Services and Servers on Internet," University of North Texas, Apr. 1995, pp. 5;.

Miller N. "State of the Art Dial 1-800-Internet", Byte, Feb., 1996, pp. 83, 84, 86 and 88;.

Babbage R. et al., "Internet Phone—changing the telephony paradigm?", BT Technol J, vol. 15, No. 2, Apr. 1997, pp. 145-157;.

Naoko I. et al. Abstract, "Voice Communications System and Voice Communication Method", Hitachi, Ltd., Application No. 05/343,162, filed Dec. 15, 1993;.

Koji M. Abstract, "Conversation/Data Alternate Communication Equipment", Oki Electric Ind. Co., Ltd., Application No. 05/004,142, filed Nov. 13, 1993;.

Voigt W. Abstract, "Incoming Call Indication to Data Terminal User—by Giving Engaged Data User Visual Display on Screen Whilst calling Party Receives Announcement", Telefonbau & Normalzeit GmbH (Teln);.

Sultan K. Abstract, "Call Waiting Method for Modem—Involves Displaying Signal Indicating Calls Waiting on User Screen, and Accepting Commands from User to Place Both Modems on Hold so User Can Answer Telephone Call".

Copy of U.S. Appl. No. 09/475,206 USPTO-Pair, pp. 72;.

Copy of Preliminary Amendment dated Oct. 10, 2001 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 13;.

Copy of Non-Final Rejection dated Feb. 14, 2003 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 15;.

Copy of Amendment dated Apr. 14, 2003 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 22;.

Copy of Non-Final Rejection dated Jul. 9, 2003 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 12;.

Copy of Amendment dated Oct. 30, 2003 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 12;.

Copy of Non-Final Rejection dated Mar. 1, 2004 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 7;.

Copy of Amendment dated Jul. 22, 2004 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 13;.

Copy of Non-Final Rejection dated Jan. 12, 2005 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 12;.

Copy of Amendment dated May 2, 2005 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 11;.

Copy of Non-Final Rejection dated Aug. 8, 2005 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 10;.

Copy of Amendment dated Nov. 10, 2005 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 12;.

Copy of Non-Final Rejection dated Mar. 7, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 11;.

Copy of Amendment dated Jul. 3, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 12;.

Copy of Supplemental Amendment dated Sep. 8, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 8;.

Copy of Notice of Allowance dated Oct. 5, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 7;.

Copy of Supplemental Notice of Allowance dated Dec. 4, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 3;.

Copy of Supplemental Notice of Allowance dated Dec. 13, 2006 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 3;.

Copy of Supplemental Notice of Allowance dated Jan. 18, 2007 in U.S. Appl. No. 09/475,206, USPTO-Pair, pp. 5;.

Altmann J. et al. "Index Project: User Support for Buying Qos with Regard to User's Preferences", IEEE, 1998, pp. 101-104;.

Dalgic I. et al. "True No. Portability and Advanced Call Screening in a SIP-Based IP Telephony System", IEEE Communication Magazine, Jul. 1999, pp. 2-20;.

Edell R. J. et al. "Providing Internet Access: What we Learn from the Index Trial", <http://www.Index.Berkeley.Edu/reports/99-010W>, Apr. 1999, pp. 1-17;.

Patel a. et al. "A Technique for Multi-Network Access to Multimedia Messages", Computer Communications, vol. 20, No. 5, Jul. 1, 1997, pp. 324-337;.

Copy of Preliminary Amendment dated Jan. 3, 2007 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 33;.

Copy of Non-Final Rejection dated Mar. 31, 2008 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 12;.

Copy of Terminal Disclaimer dated Jul. 21, 2008 in U.S. Appl. No. 11/649,054, USPTO-Pair, p. 1;.

Copy of Amendment dated Jul. 21, 2008 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 2;.

Copy of Terminal Disclaimer Review Decision dated Aug. 25, 2008 in U.S. Appl. No. 11/649,054, USPTO-Pair, p. 1;.

Copy of Non-Final Rejection dated Oct. 16, 2008 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 10;.

Copy of Amendment dated Jan. 7, 2009 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 4;.

Copy of Notice of Allowance dated Mar. 9, 2009 in U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 12;.


Copy of U.S. Appl. No. 11/649,054, USPTO-Pair, pp. 75;.

CrystaLAN, Installation Planning Guide, Release 1.2, Chapters 1-3, Shoreline Teleworks, 1999, pp. 35;.

ShoreWare Director, System Administrator's Guide, Release 1.2, Shoreline Teleworks, 1999, pp. 66.

* cited by examiner

FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8

FIG. 9



1

RESPONDING TO A CALL WITH A PROMPT AND ROUTING THE CALL TO A PHONE SELECTED IN RESPONSE TO THE PROMPT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application ("current application") is a continuation of U.S. patent application Ser. No. 12/481,250 filed Jun. 9, 2009, which is a continuation of U.S. patent application Ser. No. 11/649,054 filed Jan. 3, 2007 and issued as U.S. Pat. No. 7,564,839 which is a continuation of U.S. patent application Ser. No. 09/475,206 filed Dec. 30, 1999 and issued as U.S. Pat. No. 7,180,889, all of which are hereby incorporated by reference herein in their entirety.

RE-VISIT NOTICE

Applicant hereby rescinds any disclaimer of claim scope in the priority applications identified above (namely U.S. application Ser. Nos. 12/481,250, 11/649,054 and 09/475,206) or the corresponding prosecution histories thereof and advises the US Patent and Trademark Office (USPTO) that the claims in the current application may be broader than any claim in the priority applications. Applicant notifies the USPTO of a need to re-visit the disclaimer of claim scope in the priority applications, and to further re-visit all prior art cited in the priority applications, including but not limited to cited references over which any disclaimer of claim scope was made in the priority applications or the corresponding prosecution histories thereof. See *Hakim v. Cannon Avent Group, PLC*, 479 F.3d 1313 (Fed. Cir. 2007). Moreover, any disclaimer made in the current application should not be read into or against any of the priority applications.

BACKGROUND OF THE INVENTION

Present day telephony voice networks, have a network built around circuit switches, end offices, a toll network, tandem switches, and twisted wires. These voice networks are referred to as a public switched telephone network (PSTN) or plain old telephone service (POTS). Due to bandwidth limitations of plain old telephone service (POTS), there is an inherent inability to efficiently integrate multiple types of media such as telephony, data communication for personal computers (PC), and television (TV) broadcasts. Accordingly, a new broadband architecture is required. This new architecture gives rise to a new array of user services.

Presently the world is running out of telephone directory numbers (DNs) and IP addresses. For example, there has recently been a need to introduce new DN area codes and redistribute existing DN area codes in order to accommodate additional lines for PSTN users in the United States. Thus, a need exists to provide additional lines without using additional DNs to identify additional lines. A flexible user interface for the new broadband architecture supporting voice service has the capability to provide multiple user telephone lines associated with a single DN.

SUMMARY OF THE INVENTION

Aspects of the invention include providing broadband access capabilities or enhanced services for use in conjunction with a packetized network such as an Internet Protocol (IP) based system infrastructure.

2

Other aspects of the invention include providing one or more of the following either individually, or in any combination or subcombination:

- a new broadband architecture;
- 5 broadband network capabilities, including local access;
- enhanced services for use in conjunction with a packetized network such as an Internet Protocol (IP) based system infrastructure;
- a user interface for use the new broadband architecture supporting packetized voice service which has the capability to accommodate multiple telephone lines associated with a single DN;
- 10 a user interface for the new broadband architecture which has the capability to accommodate multiple telephone lines associated with multiple DNs;
- 15 a user interface with ports readily connected to plain old telephones (POTS);
- a user interface which provides a distinct alert for each telephone line; and
- 20 a user interface which provides enhanced greeting and message features.

A need exists to reduce the number of DNs. The user interface of the present invention can accommodate multiple telephone lines using a single DN. Thus, the user interface limits the need to introduce new DN area codes and redistribute existing DN area codes in order to accommodate additional telephone lines for PSTN users. In addition, using a single DN for multiple lines will save customers money, since a customer will only be charged for a single DN. Furthermore, the user interface may be configured to accommodate multiple lines associated with multiple DNs. A business or a residence may require more than one telephone number. Thus, configuring the user interface to accommodate multiple DNs for multiple lines can satisfy customer needs. Also, the present invention provides a user interface device for packetized voice service which may accommodate conventional POTS telephones as well as other end user devices.

Although the invention has been defined using the appended claims, these claims are exemplary and limiting to the extent that the invention is meant to include one or more elements from the apparatus and methods described herein and in the applications incorporated by reference in any combination or subcombination. Accordingly, there are any number of alternative combinations for defining the invention, which incorporate one or more elements from the specification (including the drawings, claims, and applications incorporated by reference) in any combinations or subcombinations.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a schematic representation of a broadband network (e.g. broadband IP based network) in accordance with a preferred embodiment of aspects of the present invention.

FIG. 2 shows a block diagram of a preferred embodiment of a centralized control (IP central station) in accordance with aspects of the present invention.

FIG. 3 shows a block diagram of a preferred embodiment of a local control apparatus (broadband residential gateway) in accordance with aspects of the present invention.

FIG. 4 shows a detailed schematic representation of an exemplary embodiment of the broadband network shown in FIG. 1.

FIG. 5 is a signal flow diagram illustrating a typical on-network to off-network call according to one preferred method of operating the broadband network shown in FIG. 1.

FIG. 6 is a signal flow diagram illustrating a typical on-network to on-network call according to one preferred method of operating the broadband network shown in FIG. 1.

FIG. 7 shows a block diagram of the Broadband Residential Gateway in accordance with further preferred embodiments of the present invention.

FIG. 8 shows a flow chart for a method of directing an incoming call when one directory number is mapped to multiple ports on a BRG.

FIG. 9 shows a flow chart for a method of directing an incoming call when multiple directory numbers are mapped to multiple ports on a BRG.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A new system is provided for broadband access and applications. Unless otherwise indicated by the appended claims, the present invention is not limited to the preferred embodiments described in this section but is applicable to other integrated multimedia communication systems.

I. Integrated Communication System Overview
Referring to FIG. 1, an exemplary embodiment of a broadband network 1. The broadband network generally provides interconnection between a plurality of customer locations utilizing various interconnection architectures including Internet Protocol (IP) based network, various existing systems (legacy systems) such as the public switched telephone network (PSTN), ATM networks, the Internet, signaling networks, as well as other systems. The broadband network provides versatile intelligent conduits that may carry, for example, Internet Protocol (IP) telephony or multimedia signals between the customer premises over, for example, the public switched telephone network, Internet, or wireless communication networks.

Again referring to FIG. 1, the broadband network 1 may include one or more customer premises equipment (CPE) units 102. The customer premise equipment 102 may be variously configured. In one example, the customer premise equipment 102 may include one or more local control devices such as a broadband residential gateway (BRG) 300. Although the broadband residential gateway is preferably disposed in a residence for many aspects of the invention, in exemplary embodiments, it may also be disposed in a business or other location. The broadband residential gateway 300 may be variously configured to provide one or more integrated communication interfaces to other devices within the customer premise equipment 102 such as televisions (TV), personal computers (PC), plain old telephone system (POTS) phone(s), video phones, IP enabled phones, and other devices. For example, the broadband residential gateway 300 may provide one or more telephone port connections (e.g., plain old telephone system), Ethernet connections, coaxial connections, fiber distributed data interface (FDDI) connections, wireless local area network (LAN) connections, firewire connections, and/or other connections to a plurality of devices such as plain old telephones, IP based phones, digital ISDN phones, television converters, e.g., cable television (CATV) set top devices, televisions, digital televisions, high definition televisions (HDTV), video phones, and other devices. In exemplary embodiments, the broadband residential gateway 300 may support communications between any of the aforementioned devices in intra-premises calling and/or extra-premises calling. Further, when the broadband residential gateway 300 is used in a business environment, it can function as a private branch exchange or key type telephone system. In addition, the BRG is a flexible user interface which

may be configured to provide multiple user telephone lines associated with a single DN. A user may be charged by a telephone utility for each DN. Thus, configuring the BRG to associate multiple lines with a single DN can be less expensive than having multiple DNs for a single user. Alternatively, the BRG may be configured so multiple DNs identify the BRG.

In FIG. 1, broadband residential gateway 300 is illustrated as a single physical device. This configuration is appropriate where centralization of maintenance and control is desirable. Alternatively, the broadband residential gateway 300 may be separated into more than one physical device allowing functionality to be distributed to a plurality of different physical locations in the customer premise and/or broadband network 1. However, in many embodiments, having a centralized broadband residential gateway 300 located in a single location provides ease of maintenance, control, and re-configuration as well as a reduction in cost due to shared functionality. For example, the broadband residential gateway may be configured to provide the intelligence needed to allow each of the customer premises equipment devices to operate within the broadband network 1. For example, analog voice may be converted to digital data and packetized for transmission in an appropriate output protocol such as an Internet protocol (IP).

In exemplary embodiments, the broadband residential gateway 300 may function to couple devices within the customer premise equipment 102 to the rest of the broadband network 1 using any suitable broadband communication mechanism. In the embodiment shown in FIG. 1, the broadband residential gateway 300 utilizes a hybrid fiber-coaxial plant 112 to couple the broadband residential gateway 300 to the rest of the broadband network 1. The hybrid fiber-coaxial plant 112 may be preferred in many embodiments over other broadband communication mechanisms because of the large number of homes currently connected to cable networks, the capacity for shared access, and the ability for asymmetric data access speeds which allow high quantities of data to be distributed to the various devices in the customer premises equipment 112. The hybrid fiber-coaxial plant 112 may include coaxial cable and/or optical fiber networks in any suitable combination. The hybrid fiber-coaxial plant 112 may provide an intelligent broadband conduit between the broadband residential gateway 300 and a gateway such as the head-end hub (HEH) 115. The head-end hub 115 may be variously configured to provide various services and/or interconnections with the rest of the broadband network 1. For example, the head-end hub 115 may provide an interconnection point to gather and aggregate external services (e.g., off air and satellite video, public switched telephone network voice, multimedia messages, and Internet data) for distribution to and from the hybrid fiber-coaxial plant 112. With respect to telephony and multimedia calls, the head-end hub 115 may function as intelligent conduit for connection and communication between the hybrid fiber-coaxial plant 112 and external networks such as an IP network 120 and/or an ATM/frame relay/cell relay network 185.

The broadband network 1 may include any number of interconnected head-end hubs 115, IP networks 120, and/or ATM networks 185. Further, the IP network 120 and/or ATM network 185 may be connected to one or more other networks and devices such as:

- (1) external networks including a public switched telephone network (PSTN) 160, a signaling system 7 (SS7) network 170, an Internet 180, and/or a wireless network 144;
- (2) various components including one or more private branch exchanges 146, terminals 142 including comput-

5

ers and wireless devices, and/or one or more stand alone broadband residential gateway **300**;

- (3) one or more administration centers **155**;
- (4) one or more secure network management data networks **190** such as a network operations center (NOC);
- (5) one or more billing systems **195** such as OSS; and/or
- (6) one or more centralized control centers such as what is referred to as an IP central station **200**.

The IP network **120** and/or ATM network **185** may include one or more routers and/or other devices to route, for example, telephony calls, multimedia calls, signaling messages, administrative messages, programming messages and/or computer data between the various devices in the broadband network **1** such as the head-end hub **115**, the public switched telephone network **160**, the private branch exchange (PBX) **146**, as well as the other devices discussed above. In preferred embodiments, the information traveling in the IP network **120** may be packetized and formatted in accordance with one of the Internet protocols. The IP network **120** may also include gateways to interface with the various other networks and/or devices. For example, the gateways may be distributed at the edge of the IP network where the IP network interfaces with one of the other devices or networks. Alternatively, the gateways interfacing the IP central station **200** to, for example, the Internet **180**, public switched telephone network (PSTN) **160**, signaling system 7 (SS7) **170**, wireless networks **144**, ATM/frame/cell relay networks **185** may be provided in the IP central station **200**, or in both the IP network **120** and the IP central station **200**, and/or partially distributed between the IP network **120** and the IP central station **200**. Where the gateways are separated by an IP network **200**, an appropriate transport protocol may be utilized to logically connect the IP central station **200** to the particular gateway.

The IP central station(s) **200** may be connected to, for example, one or more IP networks **120**, ATM networks **185**, secure management data networks **190**, and/or administration centers **155**. The IP central station **200** may be variously configured to include one or more servers and/or one or more gateways. In exemplary embodiments, the servers and gateways provide the necessary intelligence and traffic management capabilities to enable information, e.g., IP telephony signals, to travel through the broadband network **1**. For example, the IP central station **200** may be configured to manage voice information transfer from the public switched telephone network **160**, through the IP network **120**, and into and out of one or more devices such as those connected to a broadband residential gateway **300**. The IP central station may be configured to store various control and system information such as location, address, and/or configurations of one or more broadband residential gateways **300**, as well as other routing and call set-up information.

In exemplary embodiments, one or more administration centers **155** may be connected to the IP network **120** and provide billing and local directory number portability administration. The local number portability may be handled by one or more Local Service Management System (LSMS) which may be included in the administration center **155** and/or in the IP central station **200**. Further, the Secure Management Data Network **190** may also include a mechanism for transferring various information such as billing, call tracking, and/or customer service provisioning. Various existing systems may be utilized to provide this information such as existing billing systems (OSS) **195** and/or one or more network operations center (NOC). The network operations centers may be included in the administration center **155**, the IP central station **200**, and/or the billing system **195**. The network opera-

6

tions center (NOC) may be variously configured to include a translation server to allow communications with the various disparate entities (e.g., legacy systems) in the broadband network **1**.

The IP network **120** and/or the ATM network **185** illustrated in FIG. **1** may include one or a plurality of sub-networks. Each of the sub-networks may include its own IP central station **200** in a distributed configuration, with certain routing data replicated across all IP central stations or each sub-network may be connected to a single centralized IP central station **200**. Where the IP network **120** includes one or more sub-networks, each sub-network may be connected to multiple head-end hubs **115**. Further, each head-end hub **115** may be connected to multiple hybrid fiber-coaxial plants **112**, and each hybrid fiber-coaxial plant **112** may be connected to multiple pieces of customer premises equipment **102** and/or broadband residential gateways **300**. The IP network **120** provides an interconnected broadband network which may be utilized to transport and route packetized information to and from diverse geographic locations and may be used on a national or international basis. Further, the IP network **120** and/or ATM network **185** may utilize private network facilities and/or may be provisioned over a shared network such as the Internet.

The IP central station **200** may be configured to provide connectivity for the broadband residential gateway **300** to the Internet **180** (e.g., World Wide Web (www)), as well as connectivity to other external networks such as public switched telephone network **160** and signaling system 7 (SS7) **170** for end-to-end voice, multimedia, and data applications, for example voice over IP telephony. IP packets traveling through the IP network provide for priority so that, for example, voice packets are given priority over data packets to maintain certain VoIP telephony QoS requirements and a leased line concept for packet traffic which may have an even higher priority. However, the system is sufficiently flexible so that the priority can be dynamically altered according to customer preferences, variable billing rates, traffic patterns, and/or congestion.

A. Internet Protocol Central Station

Referring to FIG. **2**, the IP central station **200** may be variously configured. In preferred embodiments, it may be configured to ensure seamless integration of IP based communication system including the IP network **120** with the public switched telephone network **160**, signaling system 7 (SS7) network **170**, and the Internet **180** so that packetized data, for example, voice calls and information data, is properly transferred between the broadband residential gateway **300**, the public switched telephone network **160** and/or the Internet **180**. In one embodiment, the hybrid fiber-coaxial plant **112**, head-end hub **115**, and IP network **120**, provide a virtual signaling conduit for packetized voice and data which may, with the coordination of the IP central station **200**, be provided in the appropriate format between the broadband residential gateway **300** and the public switched telephone network **160** and/or Internet **180**.

Again referring now to FIG. **2**, the IP central station **200** may include a central router **210**, for example, a gigabit switch, which may be utilized to interconnect various servers and gateways contained in the IP central station **200**. The central router **210** provides for example Ethernet switching and aggregate traffic between servers, gateways and the IP network **120** and/or ATM network **185** backbone. In one exemplary embodiment, the central router **210** provides high-speed, non-blocking IP and IP multicast Layer 3 switching and routing. The IP central station **200** may include one or more of the following servers: the least cost server (LCS) **255**,

the time of day (TOD) server **212**, the dynamic host control protocol (DHCP) server, the trivial file transfer protocol (TFTP) server, and the domain name service (DNS) server **214**, the system management (SM) server **216**, the call manager (CM) server **218**, the announcement server (AS) **220**, the multimedia server (MS) **222**, and/or the conference server (CS) **224**. As illustrated in FIG. 2, the servers may be separate servers, for example the call manager server **218**, or may be incorporated into a single server. In the exemplary embodiment, the dynamic host control protocol server **131**, trivial file transfer protocol server **132**, and the domain name service server **214** are each incorporated in a single server facility. Each server in the IP central station **200** may include computer(s), storage device(s), and specialized software for implementing particular predefined functions associated with each server. In this manner, the servers in the IP central station may be provisioned as a main server and one or more back-up servers to provide redundant processing capabilities. Similarly, the router may be implemented as a main router and a back-up router with similar routing functionality.

The IP central station **200** may also include, for example, one or more of the following gateways: an element management gateway (EMG) **238**, an accounting gateway (AG) **240**, an Internet (Boarder) gateway (IG) **236**, a signaling system 7 (SS7) gateway (SG) **234**, a voice gateway (VG) **232**, and/or a multimedia gateway (MG) **230**. The IP central station **200** may utilize one or more of these gateways to provide centralized system intelligence and control of voice and/or data IP packets.

In exemplary embodiments, the dynamic host control protocol server **131** and domain name service server **214** may operate to dynamically assign IP addresses devices in the customer premise equipment **102**. Where a dynamic IP assignment scheme is used, the customer premises equipment may be provided with one or a plurality of dynamic IP assignment when activated initially, and/or at the initiation of each active secession. Where an IP address is assigned when the device is initially activated, it may be desirable to assign a single IP address to a single broadband residential gateway and assign a port address to devices connected to the broadband residential gateway **300**. In other embodiments, an individual IP address may be assigned to each device coupled to the broadband residential gateway **300**. For example, the broadband residential gateway may include and/or be coupled to one or more cable modems, IP phones, plain old telephone system phones, computers, wireless devices, CATV converters, video phones, and/or other devices which each may be assigned a unique static and/or dynamic IP address and/or a port of a one of these IP addresses. The particular protocol for allocating IP addresses and/or ports may be specified using protocols defined in the dynamic host control protocol server **131**. In exemplary embodiments, the dynamic host control protocol server **131** and DN server **214** may be configured to assign available IP addresses from address pools based, for example, on the identity or type of requesting device, the amount of use expected for the requesting device, and/or predefined assignment protocols defined in the dynamic host control protocol server **131** and DN server **214**. In centralized embodiments, it may be desirable to configure the call manager (CM) **218** to provide sufficient information such that the domain name service server **214** can distinguish between static IP devices, dynamic IP devices, registered devices, unregistered devices, and registered devices that have been assigned to a particular class of service e.g., data vs. telephony, un-provisioned, vs. provisioned, etc.

The trivial file transfer protocol (TFTP) server **132** may be configured to transfer certain information to/from one or

more broadband residential gateways **300**. In exemplary embodiments, the trivial file transfer protocol server **132** provides Data Over Cable Service Interface Specifications (DOCSIS) configuration information containing QoS parameters and other information required for the broadband residential gateway **300** to operate optimally.

The time-of-day (TOD) server **212** may include a suitable facility for maintaining a real time clock such as an RFC868-compliant time server. In exemplary embodiments, the time-of-day server **212** provides system messages and/or responses to system inquiries containing a coordinated time, e.g., universal coordinated time (UCT). The universal coordinated time may be used by any of the servers and/or devices in the broadband network **1**. For example, the broadband residential gateway **300** may use the universal coordinated time to calculate the local time for time-stamping error logs.

The system management (SM) server **216** may include responsibility for the overall operational state and functioning of components in the broadband network **1**, either alone, or in combination with other system management servers **216**. The system management (SM) server **216** may be variously configured to provide monitoring and administrative functions for devices within the broadband network **1**. For example, the system management server **216** may be configured to provide management of various database functions, memory buffer functions, and software utility functions within the broadband network **1**. Software management includes, for example, version control, generic control, and/or module control.

The least cost server (LCS) **255** may be variously configured to enable the system to determine the least cost routing of telephone and data transmission throughout the network. The least cost server **255** may also provide one or more broadband residential gateway users capability to select between, for example, cost and Quality of Service (QoS).

The announcement service (AS) server **220** may be variously configured. In exemplary embodiments, it may store and send announcements to specified destinations and/or all destinations based on instructions received by, for example, the call manager (CM) server **218**. The announcement server **220** receives, for example, Media Gateway Control Protocol (MGCP) or later signaling (e.g., H.GCP—an ITU standard Gateway Control Protocol) control messages from the call manager **218**, and sends announcements to one or more voice gateways (VG) **232** and/or the one or more broadband residential gateway **300** (e.g., using Real Time Protocol (RTP) packets). The announcement server **220** may send an announcement once, a predetermined number of times, or in a continuous loop. The announcement server **220** may detect when a phone or other device has been taken off-hook and play an advertisement or other announcement to the user. Where a user has signed-up for an advertising plan whereby phone rates are reduced in return for advertising revenue generated by the advertisements, the announcement server **220** may be utilized to track the number of individuals with a particular income, age, or other profile which hear the advertisement. The announcement server **220** may respond to requests from individual system devices such as one of the broadband residential gateways **300** and/or under control of, for example, the call manager **218**. Where the announcement server is under control of the call manager **218**, the call manager may be configured to control various operating parameters of the announcement server. For example, the call manager **218** may request that certain announcements are sent once, a specified number of times, or in a continuous loop.

In still further embodiments, announcements may be generated elsewhere in the broadband network **1**, stored as files, and distributed to one or more announcement servers via a file transfer protocol or resource such as the trivial file server **214** using one or more file transfer protocols. In many embodiments, it is desirable to store announcements in an appropriate encoding format (e.g., G.711 or G.729) within the Announcement Server. The announcement may have an audio component and/or a video component. The audio/video component may be stored using a combination of an encoding format (e.g., G.711) and/or a standard file format such as wave (WAV), MPEG, and other suitable formats.

In one exemplary method of operation, a user picks up a telephone which sends a signal to the call manager **218**. Subsequently, the call manager **218** may establish a connection to the announcement server **220** and play one or more pre-recorded and/or predetermined announcement (hypertext and/or audio). Signaling tones such as a busy signal may be played by the broadband residential gateway **300** or the call manager **218**, but Special Information Tones (SIT) and/or messages may also be included as part of an announcement file. In this way, the user experience is enhanced such that the user receives a busy message and/or hypertext announcement providing one of several options for contacting the called party. The announcement server **220** may have information entered by a user using, for example, a broadband residential gateway to provide additional information to the called party. The additional information may include the ability to leave a message, type-in a chat note, page the called party, barge-in on the call, and/or other user or system defined call handling capabilities.

The announcement server **220** may also be programmed with various system messages such as an announcement indicating that a number dialed is incorrect or that the call did not go through as dialed, that the lines are busy, that all lines between two countries are currently busy, that the called party has changed numbers, that the called parties party's phone has been disconnected, that one or more system errors have occurred, and/or other announcement messages.

The call manager (CM) **218** may be variously configured. In exemplary embodiments, the call manager **218** provides a centralized call control center for supporting call set-up and tear-down in the broadband network **1**. The call manager **218** may be configured to include trunk and line information maintenance, call state maintenance for the duration of a call, and/or user service features execution. The call manager **218** may also provide for call processing functions such as a standardized call model for processing the various voice connections such as voice over IP calls. In exemplary embodiments, a standardized "open" call model may be utilized which supports standardized application programming interfaces (APIs) to provide transport services and other user functions such as calling cards. An open application programming interface and call set-up interface in the call manager will enable third party applications to be loaded into the call manager **218** and broadband residential gateway **300**. This will facilitate the development of third party applications for enhancing the functionality of components in the broadband network **1**. For example, third parties and other equipment vendors may manufacture various broadband residential gateways **300** for use in the broadband network **1** by writing applications to support the open call model of the call manager **218**. The call manager **218** and/or broadband residential gateway **300** may also be configured to execute and/or accept commands from a standardized scripting language which may generate instructions for the call manager **218** and/or broadband residential gateway **300** to execute various func-

tions. The scripting functionality may include the ability to execute an entire call model including interfaces to the signaling system 7 (SS7) **170**, public switched telephone network **160**, IP network **120**, ATM/frame/cell relay network **185**, and/or other functions within, for example, IP central station **200** such as the multimedia server **222**, announcement server **220**, system management server **216**, conference server **224**, time of day server **212**, least cost server **255**, and/or domain name server **214**.

The call manager **218** may also be configured to maintain the call states for each call it handles (e.g., a voice over IP call) and respond to system events created by, for example, the multimedia gateway control protocol (MGCP) messages and/or integrated services digital network user part (ISUP) messages for signaling system 7 (SS7) protocol that may occur during the processing of a call. Exemplary events handled by the call manager **218** include call state changes, call feature changes/call feature triggering events, changes in the status of lines and trunks, and/or error conditions. Further, the call manager **218** may interact with devices connected to a single circuit on the public switched telephone network **160** and/or a device connected to a port of the broadband residential gateway **300**. In this manner, new devices may be added to the infrastructure and operate using the open call model contained in the call manager **218**.

The call manager **218** may also include storage for subscriber and network configuration, a cache server for faster access to frequently used data, a routing engine for selecting an appropriate routing algorithm (e.g., least cost routing), and/or a service broker which provides the data and logic for specific services. In addition, the call manager **218** may include an authentication (AC) server **245** that provides authentication of various devices, objects, packets and users in the integrated multimedia system. In this manner, a user may verify the identity of the calling or called party.

The call manager **218** may interact with the signaling gateway (SG) **234**, the accounting gateway (AG) **240**, the element management gateway (EMG) **238**, the voice gateway (VG) **232**, and the multimedia gateway (MG) **230** using any suitable protocol such as IP and an interconnection mechanism such as the central router **210**. In one preferred embodiment, the call manager **218** may be configured to utilize signaling messages such as: a) ISUP messages over Common Object Broker Architecture (COBRA) interface to and/or from signaling gateway **234**, b) MGCP, SIP—simple internet protocol, H.GCP, and/or other suitable control messages to and/or from the announcement server **220**, c) call event records in modified Radius format to the accounting gateway **240**, d) Radius (or Enhanced Radius or compatible protocol) control messages to and/or from the voice gateway **232** and/or the broadband residential gateways **300**, and e) signaling network management protocol (SNMP) messages to and/or from the element management gateway **238**.

The call manager **218** may incorporate one or more databases. For example, the call manager **218** may include database information such as (1) a resources database that provides an identification of what resources are connected to the broadband network **1** and their current state; (2) a trunk/gateway database that indicates which gateway serves what circuits in a trunk; (3) a customer database which indicates whether a call is authorized, identifies what services a line supports and determines whether a telephone number is on or off the integrated IP communication network; (4) a numbering plan/least cost routing database which provides routing information that enables the IP central station **200** to choose the correct trunk as a function of the call number; and (5) a local number portability (LNP) database that indicates the

11

North American Numbering Plan (NANP) and associated prefixes which are open for association with the number portability service; and (6) an address of the service control point (SCP) towards which requests for translating these local portability numbers should be routed.

In exemplary embodiments, the broadband network **1** includes equipment compatible with the COBRA standard. COBRA may be utilized to allow applications from a plurality of vendors to operate with each other. The COBRA standard allows a company, such as AT&T, to build its network using multi-vendor equipment and yet ensure seamless integration and operation. Some of the major areas covered by COBRA v. 2.2 includes: Inter-ORB Bridge Support, General Inter-ORB Protocol (GIOP) support, Internet Inter-ORB Protocol (IIOP) support, and Environment Specific Inter-ORB Protocol (ESIOP) support. The call manager **218** may integrate these protocols to facilitate call set-up with diverse equipment. This is advantageous in that equipment from a plurality of vendors may inter-operate over the broadband network **1** without modification.

The multimedia server (MS) **222** may be variously configured. For example, one or more multimedia servers may provide support for multimedia messaging service and/or the overall management of multimedia voice and mail messages transmitted across the broadband network **1**. The multimedia server may be configured to support e-mail (e.g., html) messages, voice mail (audio) messages, and/or video mail (audio and video) messages. The multimedia messages may include standard pre-configured system messages, advertising messages, and/or user defined messages. In either event, where the messages are stored in a centralized location, the multimedia server may provide such storage. Where the multimedia server **222** provides storage for the multimedia messages, a database may be utilized for indexing, storage, and retrieval of such messages. In exemplary systems, the user may access predetermined ones of these messages. The multimedia server **222** may utilize IP as a method of communicating with other devices across the broadband network **1**.

The conference server (CS) **224** may be configured to provide for multiparty conference calls using, for example, IP voice packets during an IP telephony or multimedia session call. The conference server **224** may include specialized software that runs on a computing platform having associated multiplexing and demultiplexing capability for segregating and aggregating user information packets. For example, the conference server may log several calls into a conference session. When information packets are sent from one or more phones, they are aggregated and sent to the other phones on the conference call. The conference server **224** may use any suitable communication protocol such as H.GCP or SIP. The conference server **224** may function to aggregate user information from two or more users onto a single call path. The conference server **224** may include one or more "call-in numbers" and be controlled from any location, e.g., a centralized operator location and/or one or more broadband residential gateways **300**. It may be desirable to have the conference server **224** configured such that some callers simply monitor the call without voice interruption while other callers have both voice transmit and receive capabilities. Where a caller is not given the privileges associated with active participation in the call, voice packets from these users are discarded. For example, a CEO may have a conference call with a plurality of financial advisors and invite the press to listen on the call without interruption capabilities.

The gateways in the IP central station **200** may be configured to provide translation of signals to and/or from the various servers in the IP central station **200**, the IP network **120**,

12

the public switched telephone network **160**, the signaling system 7 (SS7) network **170**, the Internet **180**, and/or the secured management data (SMD) network **190**. The gateways typically support one or more of the following group of functions: call processing; signaling system 7 (SS7) connectivity; billing support; OAM&P support; connection to public switched telephone network; control CoS/QoS parameters; and enhanced services.

The voice gateway (VG) **232** may be connected to the public switched telephone network **160** and operate to convert between IP based voice packets and standard public switched telephone network **160** voice traffic. Voice gateway **232** may be configured as multi-frequency (MF) or ISUP gateways on a per-T1 basis. Where multi-frequency (MF) trunks are used, one embodiment utilizes signaling between the call manager **218** and the voice gateway **232** using MGCP, SIP, H.GCP and/or other compatible protocol. Multi-frequency trunks may be compatible with Feature Group D (FGD), Operator Service (OS) Signaling protocol and/or Termination Protocol (TP).

The IP central station **200** may be variously connected to the public switched telephone network. For example, the IP central station **200** may be connected directly to the public switched telephone network using, for example a bearer channel (e.g., a T1 or T3 carrier) and/or interconnected using one or more networks such as an IP network and/or ATM/frame/cell relay network **185**. Where a T1 network is utilized, it may be desirable to utilize one or more of ISUP or MF, FGD, and OS to interconnect a service bureau in the public switched telephone network **160**. Alternatively, the service bureau in the public switched telephone network **160** may be interconnected using an alternative network arrangement such as an IP network **120** and/or a ATM/frame/cell relay network **185**. The service bureau may coordinate with the IP central station **200** in providing operator services, directory services and provisioning for 311, 611, and 711 services. Emergency 911 services may be routed to an E911 tandem switch that has the appropriate databases and interfaces with a Public Safety Answering Position (PSAP). Emergency 911 services may be coordinated by the call manager **218** and/or public switched telephone network based service bureau.

Voice gateway **232** may be router-based and include one or more voice feature cards and/or DSP Module cards to perform voice processing. The voice gateway **232** may optionally include host processors, LAN/WAN ports, Ethernet ports, T1 or E1 telephony interface cards, Voice Feature Cards with DSP Modules providing voice compression transcoding (G.711 and G.729), carrier-quality echo cancellation with 8 ms-32 ms tail length, a de-jitter buffer which adapts to delay variations in the network in order to minimize the delay, packet loss concealment that generates concealment frames for lost packets using information from previously received data, and/or tone detection and generation. This function detects Multi-Frequency (MF) tones and generates MF and call processing tones (e.g. dial tone, call-waiting tone etc.).

In exemplary embodiments, the voice gateway **232** may include T1/E1 interfaces with internal Channel Service Units (CSUs). It may also be desirable to configure the voice gateway **232** such that ISUP, MF and Centralized Attendant Services (CAS) trunks are supported with a configuration done on a per T1 basis. Additionally, multi-frequency tones and Centralized Attendant Services may utilize a "robbed bits" communication scheme where bits are "robbed" from subframes to transmit in-band signaling. The multi-frequency tones may be converted to and/or from, for example, simple gateway control protocol (SGCP) signal requests and events by the voice gateway **232**. For example, multi-frequency

13

tones and/or lower level signaling and timing functions may be translated to and/or from any of the following indications: simple gateway control protocol Notify functions, simple gateway control protocol Notification Requests, Connection requests, Modify Connection requests, off-hook and/or on-hook indications.

An Ethernet interface with a RJ-45 connector may be used to connect the voice gateway **232** to the central router **210** (e.g., Gigabit Switch or High Speed Router (HSR)). The multimedia gateway control protocol may be used as the interface between the voice gateway **232** and the call manager **218**. For example, call control, signaling, and multimedia data stream, real time protocol (RTP) connections, IP addresses, UDP ports, codec choice etc. may be configured in any suitable manner such as by using a multimedia gateway control protocol. In exemplary embodiments, audio streams may be passed directly between customer premises equipment **102** using real time protocol connections over, for example, a user datagram protocol (UDP). Thus, the multimedia gateway control protocol may be utilized to request the voice gateway **232** to initiate, cancel, and/or otherwise modify connections in order to set up and tear down RTP media streams. A similar procedure may also be utilized to request continuity tests and results.

In exemplary embodiments, it may be desirable to adapt the IP network to carry signaling system 7 (SS7) Transaction Capabilities Application Part (TCAP) messages over the IP network **120** and/or the ATM/frame/cell relay network **185**. The transport of signaling system 7 (SS7) transaction capabilities application part (TCAP) messages over the packet networks allows signaling operations to be supported by multiple connections to the same host, multiple host connections, and distributed processing of call set-up information using, for example, multiple call managers **218** in the broadband network **1**. Thus, the IP network **120** and/or ATM/frame/cell relay network may be utilized to interconnect a plurality of ESS switches to transport signaling information, voice, and/or data. In embodiments where the signaling gateway (SG) **234** is configured to support signaling system 7 (SS7) signaling transport using transaction capabilities application part (TCAP) messages, it may be desirable to include a translator for converting between multimedia gateway control protocol (MGCP) messages and transaction capabilities application part (TCAP) messages and/or ISDN User Part (ISUP) messages.

The point where ISUP and TCAP messages are terminated at a signaling system 7 (SS7) signaling gateway is defined as a Service Switching Point (SSP) to the signaling system 7 (SS7) network **170**. The call manager **218** may be configured with a standardized Application Programming Interface (API) to allow interaction with the signaling system 7 (SS7) by, for example, sending and/or receiving ISUP and TCAP messages from a service switching point (SSP). Full class 5 signaling system 7 (SS7) functionality may be included in the call manager **218** including the ability to provide all of the information necessary for billing as defined in the GR-246-Bellcore standard. The signaling gateway **234** may be arranged to perform: signaling system 7 (SS7) message handling (message discrimination, message distribution, and message routing); signaling link management (e.g., link activation, deactivation); signaling route management (managing Point Code [PC] route status based on route received management messages such as Transfer Prohibited, Transfer Allowed, Transfer Restricted, etc.); and signaling traffic management (diversion of traffic based on unavailability, availability, restriction of signaling link, route, and Point Code.) The signaling system 7 (SS7) architecture supports the nec-

14

essary redundancy component scheme for system reliability and availability during scheduled maintenance and/or software/hardware upgrades. The signaling gateway **234** may be configured to directly provide for lower level signaling system 7 (SS7) processing.

In exemplary embodiments, the signaling gateway **234** interacts with the call manager **218** using an appropriate open interface (e.g., Common Object Request Broker Architecture (COBRA)). In these embodiments, it may be desirable for translation software in the signaling gateway **234** to add Message Transfer Part (MTP) layer information to the ISUP and/or TCAP data to create a complete signaling system 7 (SS7) message. The complete signaling system 7 message may then be sent to the Signaling Transfer Point (STP) in the external signaling system 7 (SS7) network **170**. Conversely, the signaling gateway **234** may be configured to remove ISUP or TCAP application layer data from the signaling system 7 (SS7) messages received from the STP prior to converting the information to an appropriate open interface (e.g., COBRA) and forwarding the information to the call manager **218** via the central router **210**.

The accounting gateway (AG) **240** may be configured to receive messages representing events from the call manager **218** via a suitable transport mechanism such as the central router **210**. Typically, two messages are received for each call, the first when the call is established, and second when the call terminates. In the case of unsuccessful calls, only the failure message will be logged. The messages provide details about the calling and called parties, the timing of the call set-up, the duration and the quality of the call. Accounting gateway **240** may be duplicated using a redundant computer, with each gateway having dual-mirrored disks. The accounting gateway **240** stores usage records and may then distribute them to linked destinations (e.g., billing centers) for processing. Billing centers typically include bill processors that receive accounting information from the accounting gateway **240** and generate appropriate on-line or paper billing to customers. The accounting gateway may be configured to accommodate multiple days worth of accounting records such as the records for one day, two days, three days, four days, a week, or a month. The period in which the data is retained in the accounting gateway may be dependent on business needs, hardware restrictions, and/or the billing cycle. For example, as the end of the billing cycle nears, it may be desirable to shorten the period the accounting gateway holds the data such that calls placed the day the bills are printed are included on the bills. Further, the accounting gateway may both retain and forward data to the billing centers. In this manner, if the equipment at the billing center fails, the accounting gateway **240** may serve as a backup. Similarly, the billing center may act as a backup where the accounting gateway **240** fails.

An Automatic Message Accounting (AMA) format is typically used by circuit-switching systems, packet-switching systems, and other network elements to provide billing usage measurements data (e.g., the Bellcore® Automatic Message Accounting Format (BAF)). This data may be utilized either to permit charging the customer for use of network resources or to permit charging other carriers (e.g., InterExchange Carrier (IEC) and other Local Exchange Carrier (LEC)) for assistance in placing call connections. The accounting gateway **240** may be configured to convert this information into an Automatic Message Accounting Format (AMA) Format (e.g., BAF) records and send these records to the external billing systems using, for example, a TFTP (trivial file transfer protocol). Time-stamp accuracy is typically based on the accuracy of the call manager **218** clock which may be derived from the TOD **212** server. To create appropriate AMA records, the

15

event information produced by the call manager **218** preferably has appropriate information for the telephone service specified such as phone number of the calling party (customer), phone number of the called party (customer), time of call, duration of the phone call, and use of any discretionary features. Different AMA structures may be generated between On-Net calls (defined as within a network service provider IP network **120**) vs. Off-Net calls (defined as outside of service provider IP network—e.g. public switched telephone network) for billing purposes.

The element management gateway (EMG) **238** may provide system management functionality that includes, for example: a) status and performance monitoring for the Operation Administration, Maintenance, and Provisioning center, to gauge the ongoing operation of applications; b) extensive information exchange with a network operations center responsible for ongoing maintenance of one or more applications; c) customizable operations interface to allow the network operations center to view only information required, thus reducing the time spent filtering information; d) centralize distributed application configuration allowing for the centralized configuration of objects residing on a plurality machines; e) proactive network management capabilities to remove the need for constant operator intervention making the day-to-day operations more efficient; and/or f) intelligent display of status information to separate critical issues from low-priority problems allowing the operation center to assign resources to the right problems at the right time.

The multimedia gateway (MG) **230** may be configured to connect to the public switched telephone network **160** and to convert IP based multimedia packets into standard public switched telephone network **160** traffic. The multimedia gateway **230** may include an intelligent trunking interface that communicates with the call manager **218** for automatic trunk sizing and allocation between the IP network **120** and the public switched telephone network **160**. For example, when an system user at the customer premises is using a PC and/or a multimedia phone to communicate with a traditional public switched telephone network **160** user, the communication session involves the transmission of video and audio data. The bandwidth that is required for this type of communication is much greater than that required for a PSTN-to-PSTN voice call or an IP-to-PSTN voice call. The multimedia gateway **230**, as the interface between two systems, may negotiate a larger bandwidth to facilitate the call if the called party is also video enabled. This bandwidth negotiation process typically occurs with a 5ESS or a Local Digital Switch within the public switched telephone network **160**. Typically, a multimedia call, including live video, audio and data, will require bandwidth ranging from 56K to 1.544 Mbps. However, as the number of users sharing the same link grows, the quality of the transmission deteriorates significantly. The multimedia gateway **230** must be able to monitor bandwidth usage and make appropriate adjustments so as to maintain an acceptable quality of service. Further, it may be desirable for the call manager **218** and the multimedia gateway **230** to communicate between themselves and/or the customer premises equipment **102** to determine whether the user has authorized the additional bandwidth and hence expense of the call. For example, even where a called and/or calling party is video enabled, it may nonetheless refuse to authorize payment for the increased bandwidth necessary for video.

The Internet gateway (IG) **236** may be connected to the Internet (e.g., World Wide Web (www)) and provide a means for IP based data packets to be routed between the IP network **120** and the Internet **180**. Alternatively, IP based voice pack-

16

ets may be routed via the Internet **180**. In exemplary embodiments, the Internet gateway **236** routes data-only packets which share the same priority level with other lower priority, non-real-time traffic consistent with computer data communications presently experienced with the Internet **180**. Consequently, low priority and low latency data traffic on the IP network **120** utilize the Internet gateway **236** to communicate with other IP data networks such as the www. Voice packets may be routed through another network such as the ATM/frame/cell relay network **185**, a private IP network **120**, and/or the public switched telephone network **160** where committed information rates may be easily obtained.

In exemplary embodiments, the broadband network **1** includes the interfaces which enable connections to existing Operation, Maintenance and Provisioning (OAM&P) **195** systems that support, billing, accounting, provisioning and/or configuration management functions. A Secured Management Data (SMD) Network **190** may be utilized to connect the OAM&P **195** to the accounting gateway **240** and element management gateway **238**. The Secure Management Data network **190** may include a Network Service Division's NSD Net. The Secure Management Data network **190** helps ensure that only secure communication can occur between the IP central station **200** and the OAM&P **195**. This eliminates one potential means of tampering with the billing and provisioning functions in the OAM&P. The billing systems (OSS) **195** may include the Network Operations Center (NOC). The NOC may include a translation server which includes functions for allowing communications and control of diverse networks.

B. Broadband Residential Gateway (BRG)

Referring to FIG. 3, a preferred embodiment for a broadband residential gateway (BRG) **300** will now be described and explained. The broadband residential gateway **300** may be configured as the interface unit between the remainder of the customer premise equipment **102** devices and the external network. The broadband residential gateway **300** may be connected to the remainder of the broadband network **1** using any suitable mechanism such as a gateway directly into an IP network and/or a cable connection. In the most preferred embodiments, a hybrid fiber-coaxial plant connection is utilized such as hybrid fiber-coaxial (HFC) plant **112**. The hybrid fiber-coaxial plant **112** allows numerous broadband residential gateways **300** to be included on an existing hybrid fiber-coaxial plant **112** without modification to the plant's infrastructure.

The broadband residential gateway **300** may be variously configured to, for example, provide high-speed cable modem capabilities to interconnect one or more associated PCs with each other and with the remainder of the broadband network **1**, provide functionality to one or more TVs (using, for example, either an integrated or separate decoder functionality, e.g., set top box **350**), one or more telephone connections such as plain old telephone service (POTS) phones and/or digital telephones, displays, wireless interfaces, voice processing, remote control interface, display interface, and/or administrative functions. In exemplary embodiments, the broadband residential gateway **300** may a) providing conversion between analog voice and IP voice packets, b) multiplexing/demultiplexing streams of IP voice packets, c) supporting multiplexing/demultiplexing of multiple incoming and outgoing signals including multiple voice, multimedia, data, system administration, and/or TV information signals.

Where the elements of the broadband residential gateway **300** are interconnected, the interconnection may be provided by one or more data buses, for example, a high speed bus (HSB) **360**, processor bus **380**, and/or other interconnection

17

system. The high speed bus **360** may be configured to provide a flexible conduit for transferring information between the internal hardware, processors and ports. In exemplary embodiments of the broadband residential gateway **300**, the high speed bus **360** may include one or more of the following functional units a) a universal remote control receiver module **365** for receiving wireless (e.g., infrared, and/or RF) signals (e.g., keyboard signals and/or remote control signals) for control of the broadband residential gateway **300** and/or any connected devices, b) a display, display driver, touch screen logic module for driving one or more local and/or remote displays for interfacing with the broadband residential gateway **300** and/or one or more connected devices, c) one or more TV port modules **336** for interconnecting televisions, set-top devices, and/or other audiovisual devices to the broadband residential gateway **300**, d) one or more data port modules **334** for connecting/interconnecting data enabled devices (e.g., personal computers, palm top devices, etc.), e) one or more telephony port modules **332** for interconnecting one or more analog and/or digital telephones, f) one or more peripheral port modules **342** for interconnecting one or more peripheral devices such as disk drives, data storage devices, video cassette recorders, DVD devices, audio devices, video devices (e.g., camcorders, digital cameras, digital video recorders, stereos, etc.), g) one or more external/internal intercom modules **344** for interconnecting remote intercom and/or security monitoring devices, h) one or more wireless interface modules **345** for interconnecting with various wireless extension devices such as wireless TVs, cordless and/or wireless telephones, wireless LANs, etc.) one or more voice recognition/voice synthesis modules **355** for generating voice announcements, voice messages, and voice prompts and for recognizing voice generated commands and data, j) set-top box module **350** for performing the functions associated with a set-top box locally and/or for communicating with one or more remotely coupled set-top boxes, k) memory **322** (e.g., DRAM, RAM, flash, and/or other memory) for storing information and operating data within the broadband residential gateway **300**, l) transceiver **302** for communicating with one or more external broadband networks m) operating program store **330** (e.g., ROM, flash, etc.) for storing at least portions of the operating programs for the broadband residential gateway **300** and/or interconnected devices, n) security processor, smart card and/or credit card interface module **340** for providing secure processing functions and/or credit card/smart card transaction functions, and/or o) distributed processing controller **306** which may be a microprocessor and/or one or more interconnected distributed processing modules for controlling the broadband residential gateway **300**. Where the distributed processing controller **306** includes one or more distributed processing modules, the modules may include a telephony processing module (P1) **308**, data processing module (P2) **310**, video processing module (P3) **312**, auxiliary processing module (P4) **314**, IP processing module (P5) **316**, and/or an operations administration maintenance and provisioning processing module (P6) **318** interconnected through one or more busses such as processor bus **380**. The processor bus **380** and/or high speed bus **360** may include any suitable interconnect bus including intelligent bus configurations incorporating smart buffer logic (not shown in FIG. 3) to facilitate data transfer between interconnected processors and/or modules. The various modules and/or processing components of the broadband residential gateway **300** may be powered by, for example, a power supply unit (not shown). Each of the individual modules of the broadband residential gateway will now be described in more detail.

18

The transceiver **302** may include circuits for converting digital signals to and from RF signals suitable for transmission across a broadband network such as the hybrid fiber-coaxial plant **112**. The transceiver **302** may include one or more input/output ports such as a cable interface (e.g., an F connector cable connection) and/or a fiber optic interface connected to a communication media (e.g., hybrid fiber-coaxial Plant **112**). The transceiver **302** may be compatible with the DOCSIS 1.0 or later specifications. For signaling purposes, the broadband residential gateway **300** may be compatible with the Media Gateway Control Protocol (MGCP) or other compatible signaling protocol (e.g., SIP or H.GCP) to support telephony applications. The transceiver **302** may serve as a modem, a translator and/or a multiplexor/demultiplexor. Data received from the network may be de-multiplexed and placed on the data bus for dispatch to the appropriate peripherals and/or ports. Data from the various ports and peripherals may be multiplexed together for distribution over one or more broadband networks (e.g., the hybrid fiber-coaxial (HFC) plant **112**). Where a hybrid fiber-coaxial plant **112** is utilized, the data may be multiplexed onto various frequency bands of the hybrid fiber-coaxial plant **112** in a continuous data stream(s) and/or packetized data stream(s). To facilitate data transfer for various networks, the transceiver **302** may include one or more registers for data queuing and/or IP tunneling of data packets across the broadband network.

Although the illustration of a display, display drivers, and touch screen logic device **338** suggests that the a display is integral to the broadband residential gateway **300**, alternative embodiments of the broadband residential gateway **300** may provide a user interface via the TV screen, PC screen, video telephone, and/or other display device in addition to, or in lieu of, a display integral to the broadband residential gateway **300**.

The peripheral ports module **342** may include a plurality of ports providing connectivity to external peripherals. Exemplary interfaces include, PCI, Firewire, USB, DB25, etc. Devices which incorporate one or more of these interfaces may utilize the broadband residential gateway **300** to interconnect to the remainder of the broadband network **1**.

The external/internal Intercom Module (IM) **344** may include one or more microphones/speakers, voice CODECS, telephony processors, and/or interface ports. Where an intercom module **344** is utilized, the built-in circuitry may be configured to detect, for example, unused plain old telephone system telephone(s) and generates a special intercom tone on these unused telephones. In this manner, existing plain old telephone system telephones, digital phones, and/or other devices may serve as an intercom throughout the residence. The controller **306** (e.g., such as the P1 telephony processor **308**) may function to command the intercom module **344** to determine an appropriate intercom path to select an intercom connection between various locations. In exemplary embodiments, the CODEC may be configured to convert the analog voice signal into IP packets for transmission over one or more data ports **334**, TV ports **336**, display modules **338**, telephony ports **332**, peripheral ports **342**, external/internal intercom ports **344**, wireless interface ports **345**, and/or set-top boxes **350**.

In yet further embodiments, multiple broadband residential gateways **300** may be configured through, for example, IP tunneling, to set-up an intercom connection between multiple remote broadband residential gateways **300**. In this manner, an administrative assistant at the office may be contacted via an intercom connection present at the user's home. Thus, one or more individuals disposed at either local and/or remote

locations with diverse types of equipment may communicate as an intercom group without the need to communicate via normal dialing procedures.

In addition to intercom services, the intercom module **344** may also configure intercom services for other telephony services (e.g., extension transfer, call conferencing, internal caller ID), high speed data services (e.g., LAN connections), facsimile transmission/reception, e-mail transmission/reception, video conferencing, and/or CATV/HDTV (Cable Television/High Definition Television) using standard industry protocols such as DOCSIS 1.0 or higher and IP tunneling transmissions. These services are advantageous in that once configured, the user may simulate a work environment in his home.

Though processing may be accomplished by a single processor performing all functions (e.g., processing controller **306**), in the preferred embodiment shown in FIG. 3, the architecture employs a distributed processing controller **306**, and a plurality of processors **P1-P6 308-318**. In the distributed processing architecture, each of the plurality of processors **P1-P6** may be configured to have a dedicated function to provide predetermined services or applications. The processors may be coupled together via any suitable mechanism such as the processor bus **380** and/or high speed bus (HSB) **360**. The first processor **P1 308** may include telephony applications such as call set-up, call tear down, and call functions; the second processor **P2 310** may include management functions such as distribution and coordination of data within the various devices of the broadband residential gateway **300**; the third processor **P3 312** may include video processing functions for configuring control panels, screen displays of attached devices, video conference calls, MPEG decoding functions and other video processing functions; the fourth processor **P4 314** may include an auxiliary processor for offloading special processing functions such as numeric processing; the fifth processor **P5 316** may include interface input/output processing (e.g., text to voice and vice versa) and/or Internet protocol (IP) processing functions for configuring data to communicate with the remainder of the broadband network **1** and/or devices attached to the broadband residential gateway **300** such as IP telephones or IP enable PCs; and the sixth processor **P6 318** may include processing functions for Operation, Maintenance and Provisioning (OAM&P) processing. Each of the above processors may be an entirely separate processing unit with included RAM, ROM, Flash memory, or may share RAM, ROM, and/or Flash memory. Where shared RAM, ROM, and/or Flash memory is utilized, the memory may be located within the distributed processor controller **306** and/or on the processor bus **380**. Alternatively, the memory may be integrated into the operating program store **330** and/or into memory **322**.

The Distributed Processing Controller **306** with its associated processors (**P1-P6**) may be coupled to the various elements of the broadband residential gateway **300** so as to enable proper operation of each of the individual components. For example, the distributed processing controller **306** (with any associated processors (**P1-P6**)) may also be coupled to the security processor, smart card/credit card, and interface module **340**, the peripheral port(s) module **342**, and/or the External/Internal Intercom Module **344** for providing control and coordination among devices coupled to the high speed bus **360**.

The display **338** may include, for example, an interactive LED/LCD module positioned in a suitable location such as within or attached to the broadband residential gateway **300**. The display **338** may include an interface to notify, display and receive user inputs and processing status. The display **338**

may be configured to display various informational status such as multimedia mail, called ID, call logs, call in progress and associated information, call waiting information, call conferencing, and/or other call related information. The display **338** may provide a display of real time status of the various devices connected to the broadband residential gateway **300** as well as any current connections, calls, and/or data transfers. The display **338** may also include touch screen capabilities that allow information to be input via a plurality of interrelated on-screen prompts, on-screen icons, and/or a keypad (e.g., an alphanumeric keyboard). The keypad may be a remote control, numeric keyboard, and/or alphanumeric keyboard.

In one embodiment of the display **338** operation, a user may touch an icon representing a pending voicemail and/or multimedia mail message. The panel may be configured to send an electronic signal to the processing controller **306** and/or an attached processor such as the telephony processor. On receiving the signal, the **P1** telephony processor **308** may be configured to generate an IP packet via the transceiver **302** across portions of the broadband network **1** to the multimedia server **222** in IP central station **200**. The multimedia server **222** may authenticate the request by, for example, verifying location of the request and/or the identity of the requesting party. Where identity of the calling party is being verified, the user enter an access password by an audio and/or keyboard request. Where an audio request is generated, the user may utilize the external/internal intercom module **344** of the broadband residential gateway **300**, or via a text message entered into the display **338**. The user may then enter the appropriate access code via the onscreen soft keypad, microphone, and/or keyboard. Alternatively, the message could be stored locally in the broadband residential gateways **300** memory **322** and depending on whether there is a password lock on the broadband residential gateway **300**, the user may not have to enter a password to access the message. Where the message is stored locally in the broadband residential gateways **300** memory **322** rather than IP central station, the display **338** simply recalls the message from memory and presents to the user to provide one-touch instant message retrieval.

In embodiments where the broadband residential gateway **300** supports multiple mailboxes, the icons on the LCD/LED may be personalized to show the identity of the owner of the message. Each user may have a different password to ensure privacy of access. An activity log which tracks past and present messages and/or archives multimedia messages may be presented on display **338**. The archive may be stored locally, or at a remote location such as IP central. The archive may be utilized by the user to recall messages which have long since been erased from local storage but may be retrieved from IP central on tape and/or disk storage. This is preferably an optional feature for those users who are less security conscious. The multimedia messages need not be displayed only on display **338**. In alternate embodiments, any of the peripheral devices attached to the broadband residential gateway **300** are capable of receiving the multimedia messages.

The memory **322** may be variously configured to include one or more field-upgradeable card slots for permitting memory expansion. Certain users may wish to enable higher end applications such as near video on demand (e.g., pausing of shows via buffering in memory), video conferencing of multiple users, multi-party conferences, call waiting for multiple parties, etc. Accordingly, the use of a broadband residential gateway **300** allows the user to upgrade memory via inserting additional cards. Alternatively, the user may use system memory in IP central and buffer data remotely.

Operating program store **330** may be configured to receive updates. This may be accomplished by having the user replace one or more memory cards or automatically by the IP central station downloading new operating code into one or more residential gateways **300**.

As previously indicated, smart buffer logic (SBL) may be coupled to the telephony port(s) **332**, data port(s) **334**, TV port(s) **336**, peripheral port(s) **342**, and/or the distributed processing controller (DPC) **306**. Where the smart buffer logic is utilized, it may function to buffer the IP packets for delivery over the communication network such as the hybrid fiber-coaxial plant **112**. In addition, the smart buffer logic may include selectable switching and routing algorithms based on services and applications associated with each port. Depending on the destination of the IP traffic, the smart buffer logic may multiplex signals from various devices to effect faster information transfer. The smart buffer logic may also allow direct memory access between memory **322** and one or more of the devices and/or ports coupled to the high speed bus **360**.

The telephony port(s) **332** may include various interface circuitry (e.g., analog interface, logic and firmware for interfacing with the Plain Old Telephone (POTs) telephones). Also the telephony port(s) **332** may also be configured to include user interface logic, voice processing logic, voice activity detector logic, voice CODECs, and DTMF (dual tone multi-frequency) tone sensing logic. Echo cancellation and automatic gain control may also be utilized in the telephony port(s) **332** circuitry. In one embodiment, RJ-11 connectors for a plurality of lines (e.g., 4) are provided for connection to one or more existing plain old telephone system **110** telephone units. However, the broadband residential gateway **300** may contain any number of telephone connection ports. In this manner, any number of existing user phones may be connected directly to the broadband residential gateway **300** without modification. Alternatively, the broadband residential gateway can be configured to support, in addition to or as alternative to the plain old telephone system telephone units, ISDN telephones and/or other digital phones (e.g., IP telephones) using an appropriate interface.

The data port(s) **334** interface may be variously configured. In one configuration, the data ports include high speed data service connections to, for example, a personal computer (PC) using a LAN connection. For example, the data ports **334** may include an Ethernet 802.3 connection compatible with category 5 unshielded twisted pair (UTP) cable and a RJ-45 connector. The data port(s) **334** may include the necessary interface circuitry for coupling to remote computers.

The TV port(s) **336** may include an interface for conventional television, HDTV and/or CATV services. The TV port(s) **336** typically have one or more F-connectors used for coaxial cable connection to a TV set(s). The TV ports may be configured to connect to a set top box (STB) via the F-connector or directly to a remote television. In embodiments where the settop box is co-located with the television, the data supplied over the TV ports may be either analog and/or digital information. Where the settop box is integrated into and/or comprises the broadband residential gateway **300**, the TV ports may be analog or compatible with HDTV signals.

The broadband residential gateway **300** need not necessarily be limited to home use and is intended to also be utilized in business applications. In some configurations, the broadband residential gateway **300** may serve the same functions and operate as a private branch exchange (PBX). Where greater capacity is desired, one or more broadband residential gateways **300** may be disposed on a PC card and combined in a PC, rackmount, and/or server to create an expandable pri-

vate branch exchange type system that enables intra-premises calling between telephones connected to various telephone connectors on the broadband residential gateway **300**.

C. Integrated Broadband IP Based Communication System

FIG. 4 shows an exemplary embodiment of the broadband network **1** shown in FIGS. 1-3, with like components identified with identical numbers. At the extremities of the integrated communications system is the customer premises equipment unit (CPE) **102**, e.g., one or more customer premise equipment **102** at each customer location. The customer premise equipment **102** may be configured to include an integrated communication interface device such as the broadband residential gateway **300**. Other customer premise equipment **102** devices such as one or more televisions (TV) **106**, personal computers (PC) **108**, and telephones **110**, etc., may be connected to the broadband residential gateway **300** via various ports as discussed above. The customer premise equipment **102** could include multiple TVs **106**, telephones **110**, and PCs **108** connected to a single and/or multiple broadband residential gateway **300**. Further, in certain embodiments, it may be desirable to divide the broadband residential gateway **300** into more than one physical package. In this manner, certain interface circuitry may be located outside of the home while various processing circuitry may be located near a peripheral device such as in a settop.

Where the broadband residential gateway **300** is coupled to the hybrid fiber-coaxial plant **112** in accordance with a preferred embodiment of the present invention, it may be configured to provide the user with both information data (e.g., through an Ethernet interface), telephony access, and TV service (e.g., HDTV, Digital TV and/or CATV services). In exemplary embodiments, the hybrid fiber-coaxial plant **112** typically includes both coaxial cable and optical fiber networks, though, where desired, the network may include only coaxial cable or optical fiber. The hybrid fiber-coaxial plant **112** may be coupled to a head-end hub (HEH) **115**. The head end hub **115** may provide an interconnection point to gather and/or transform external services (e.g., off air and satellite video, public switched telephone network voice, and Internet data) into a format suitable for distribution on the hybrid fiber-coaxial plant **112** for use with the customer premise equipment **102**. The head-end hub **115** may include one or more cable modem termination systems (CMTS) **116** coupled between the hybrid fiber-coaxial plant **112**, a Head-end (HE) **117** and/or an Edge Router (ER) **118**. The edge router **118** may be coupled to the cable modem termination system **116** and to one or more ultra high speed routers (UHR) **121**. One or more ultra high speed routers **121** may be interconnected to each other and/or through a centralized mechanism such as an IP network database to form a high speed network. The high speed packet network **120n** is one example of the network **120** (e.g., IP network) shown in FIG. 1.

In the embodiment shown in FIG. 4, the high speed network **120n** includes the ultra high-speed routers (UHR) **121** configured in a ring configuration. Although this embodiment shows the use of the IP network database (IND) **122**, other configurations are also suitable. Where an IP network database **122** is utilized, it may be desirable to incorporate one or more data sets such as: a IP local number portability database (IP LNP) which may be utilized for transferring local DN among service providers when a user changes their service provider; an IP caller name database (IP CNAME) which may be utilized to provide a database of names relating to IP addresses and/or domain names; an IP line information database (IP LIDB) which may provide alternative billing and allow flexibility in determining who pays for a call; and an IP 1-800 Database (IP 8YY) which may provide a database of

1-800 numbers relating to the IP network **120a**. Alternatively, the IP local number portability database may be located at another location, such as at an IP central station (IP Central) **200**. Where desired, a local service management system (LSMS) **150** may be arranged to provide management of the IP local number portability database. Where a local service management system **150** is utilized, a plurality of local service order administration (LSOA) units **152** may be coupled to the local service management system by, for example, a number portability administration center (NPAC) **151**. In this manner, directory numbers may be transported among different service providers. In such a case, a NPAC **151** is generally coupled to the LSMS **150** and uses the LSMS **150** to synchronize the numbering databases and to coordinate the porting process.

As indicated above, the broadband network **1** may include a plurality of interconnected high performance networks **120n**. Each high performance network **120n** may include a separate IP central station **200** and/or share a single IP central station. Having distributed IP central stations located throughout the broadband network **1** provides improved performance and quicker response time for an individual user. Although not illustrated, each high performance network **120**, **120n** may be connected to multiple head-end hubs **115**, each head-end hub **115** may be connected to multiple hybrid fiber-coaxial plants **112**, and each hybrid fiber-coaxial plant **112** may be connected to a plurality of customer premises equipment **102**, each containing one or more broadband residential gateways **300**. The plurality of high performance networks **120n** may be configured as an interconnected network for routing packetized information from point-to-point in accordance with a desired destination.

The high performance network **120n** may be configured to provide connectivity for and between a plurality of head-end hubs **115** and/or a plurality of broadband residential gateways **300** and other networks such as the Internet, e.g., www **180**, the public switched telephone network (PSTN) **160** and/or various signaling systems such as the SS7 network **170** for end-to-end voice over IP applications. The IP central station **200** may be configured to provide seamless integration and control of the high performance network **120** (e.g., an IP based communication system) interface with the public switched telephone networks (PSTN) **160**, signaling system seven (SS7) **170**, and/or the Internet **180** so that packetized data, voice calls, and other signaling information is properly transferred between the broadband residential gateway **300** and the public switched telephone network **160** and Internet **180**. In certain configurations, the hybrid fiber-coaxial **112**, head-end hub **115**, and high performance network **120**, provide a signal conduit for packetized voice and data which may, with the coordination of the IP central station **200**, be provided in the appropriate format between the broadband residential gateway **300**, the public switched telephone network **160**, and/or the www **180**.

D. General Operation of Integrated Communication System

The typical home user is currently required to purchase multiple intelligent data conduits such as multiple set-top boxes, a plurality of conventional, DSL and/or ISDN phones, cable modems, HDTV receivers, satellite receivers, home PC LANs, etc. The integrated communication system of the present invention provides a user friendly versatile communication system that enables voice over IP telephony, information data (e.g., PC and Internet), and television services in a system with one intelligent customer premise equipment **102** interface, the broadband residential gateway **300**. The broadband residential gateway **300** in conjunction with the IP

central station **200** provides a flexible communication system that can provide any number of integrated communication service features and functions without requiring the user to become familiar with numerous, diverse types of equipment.

In one exemplary application of the voice over IP operations, the broadband residential gateway **300** digitizes the analog telephony signal using, for example, G.711 μ law coding (64 Kbps Pulse Code Modulation). The digital samples may then be packetized in, for example, the broadband residential gateway **300** into IP packets. The broadband residential gateway **300** may be configured to encapsulate the IP packets into, for example, DOCSIS (Data Over Cable Service Interface Specifications) frames for transmission back to the head-end hub (HEH) **115** over the hybrid fiber-coaxial plant **112**. The hybrid fiber-coaxial plant **112** may then be configured to transport signals for both upstream (to head-end hub **115**) and downstream (to the broadband residential gateway **300** and customer premise equipment **102**) directions. Although the DOCSIS protocol is utilized in this example, any future protocol may also be used for the digitizing and packaging of data. Where the protocol changes, it may be desirable to download new operating code from, for example, IP central station **200** to the individual broadband residential gateways **300**, to update the communication protocols dynamically. When new protocols are adopted, the IP central station may utilize, for example, the system management server **216** to download new protocol data into, for example, the protocol manager in the call manager **218** and the program store **330** in the broadband residential gateway **300**.

Where voice packets are sent over constant bit rate (CBR) channels using unsolicited grants, additional packet data channels may be used to support signaling messages (e.g., SGCP, Simple Gateway Control Protocol), high-speed cable modem service and/or other upstream packet data services. The upstream packet data services may be sent using available bit rate (ABR) channels such that the voice channels not impacted by data traffic.

A. TV Signal Reception

The head-end **117** may originate CATV signals for transmission over the distribution network. However, in alternate embodiments, signals may be inserted at other points in the distribution network, such as at various hubs or may arise at remote locations in the network such as IP central. Down stream channels may be utilized to facilitate the transmission of signals from the head-end or other input distribution point to the subscriber premise. Where analog RF signals arrive at the broadband residential gateway **300** of the customer premise equipment **102**, typically, the transceiver circuitry **302** will detect if the signal is addressed to this broadband residential gateway **300**. If so, the transceiver will allow reception of the RF signal. Upon conversion to a digital format, the signal is typically output over the high speed bus (HSB) **360** to one or more associated devices for processing. For example, where the signal is a TV signal, the signal may be output directly to the TV port **336** and/or processed by the settop box **350** prior to outputting to the TV ports **336** and/or display **338**. Where user channel selection is performed directly in the broadband residential gateway **300**, channel selection may be performed by remote control receiver **365** using an external device such as a remote control. The remote control receiver may receive a plurality of individually coded remote control commands from different receivers and process the signals for only one associated device in accordance with the received commands. Alternative channel inputs include the display **338** and/or any associated keypad. Authorization to certain channels may be controlled by security processor **340**.

25

Where a remote settop box is utilized, the box may be coupled directly to the HFC for individual frequency tuning and/or receive a digital feed from the broadband residential gateway **300** after decoding the digital signal. For example, where hybrid fiber-coaxial plant **112** contains fiber connections to locations near the individual homes, it may be desirable to download one or more simultaneous individually requested programming stream(s) and/or digital data stream(s) to the broadband residential gateway **300**. In this manner, the number of channels, movie selections, and/or entertainment options available to the user are unlimited. Cost is minimized since only a single intelligent user interface is used in the home and all televisions, phones, computers, and/or other user interface devices use the same intelligent user interface to the broadband network **1**. In this manner, the broadband network **1** may offer premium television, voice and/or data services to multiple conventional televisions, phones, and PCs without the use of multiple set boxes, modems, and external connections. Thus, the users are provided a single unified interface to satisfy their external data needs.

B. Exemplary Call Flow of an On-Network Call to an Off-Network Call, with the Off-Network Call initiating the Dropping.

FIG. **5** illustrates an exemplary call processing sequence for an on-net call (e.g., an IP based call) to an off-net call (e.g., a public switched telephone network based call), in which the off-net party initiates the drop call sequence. The exemplary call processing sequence operates as follows:

1. Once the broadband residential gateway **300** detects an off hook condition, the broadband residential gateway **300** may generate an off hook signal **508** to the call manager (CM) **218**. The off hook signal acts as a dial tone request to the call manager **218**. Alternatively, the broadband residential gateway **300** may collect all dialed digits before activating the off hook condition. This alternative may be desirable to save resources at the call manager **218** where multiple incoming lines are available to handle any additional calls. Thus, even though one phone is off-hook, the broadband residential gateway **300** determines that other lines are available and does not initiate the off-hook signal until all dialing digits have been collected.
2. Where the call is managed entirely by the call manager, the call manager **218** will issue a dial tone message **509** to the requesting broadband residential gateway **300** in order for the broadband residential gateway **300** to generate a dial tone to the associated phone. Where the broadband residential gateway **300** shares management of the call, the broadband residential gateway **300** generates the dial tone in response to the off-hook condition.
3. Where the call is managed entirely by the call manager **218**, the call manager **218** will then enter a state where it polls and collects the dialed digits **510** from the broadband residential gateway **300**. The dialed digits may then be transferred to the call manager **218** one at a time as they are entered. Alternatively, where the call set-up control process is shared between the broadband residential gateway **300** and the call manager **218**, the broadband residential gateway **300** collects the dial digits and transfers these, together with the off-hook signal to the call manager **218**. This transfer may be facilitated by combining this data into a single data packet.
4. On receiving the dialed digits, the call manager **218** will determine whether local number portability has been enabled. Where local number portability has been enabled, the call manager **218** may issue a local number

26

portability (LNP) query **511** to the IP local number portability database **122**. The IP local number portability database **122** may then supply the call manager **218** with a routing number **512** if the dialed digits form a valid sequence. Where the dialed digits do not form a valid sequence, the call manager **218** will return an error indication to the broadband residential gateway **300**. The error designation may include a tone and/or a more detailed error message for display on, for example, display **338**.

5. Where the call sequence is valid, the call manager **218** may issue a first call proceeding message **513** to the broadband residential gateway **300** indicating that the number is valid and the call is proceeding (e.g., a valid on-hook condition).
6. Next, the call manager **218** typically determines whether adequate network resources are available to carry the call. In embodiments where the broadband residential gateway **300** is connected to a hybrid fiber-coaxial plant **112**, the call manager **218** may send an open gate allocation request **514** to the cable modem transmission system **116**. In this event, it is often desirable for the cable modem transmission system **116** to provide a gate allocation acknowledgement **515**. A gate allocation acknowledgement may be utilized to verify that the necessary gate resources have been allocated.
7. The call manager **218** may send an open connection request **516** to the voice gateway (VG) **232** in order to provision the connection. Once the connection is provisioned, the VG **232** may provide an open connection acknowledgement **517** back to the call manager **218**.
8. For off network connections, it is often necessary to enter a second phase of the connection process involving the appropriate link signaling to establish a call. For example, the call manager **218** may send an ISUP IAM (Initial Address) message **518** containing the directory number (DN) of the called party to the signaling gateway (SG) **234**. This process is often utilized to allocate the appropriate voice trunk for communication. The call manager **218** may also send an alerting message **519** to the broadband residential gateway to produce an alerting signal, e.g., a ringing tone. The signaling gateway **234** may make the appropriate connections when the trunk has been allocated and acknowledge the request with an ISUP A call manager (Address Complete) message **520**.
9. Once the called party has answered the call and connection is established, the signaling gateway **234** may send an ISUP ANM (Answered) message **521** to the call manager **218** indicating that the called party has answered.
10. The call manager **218** may then send a call start message **522** to the accounting gateway (AG) **240**, indicating the start of the call. The AG **240** may use this information for billing purposes.
11. At this point, the link has been established and the conversation **523** can proceed over the communications path. Note that although signaling system 7 (SS7) signaling is used herein to illustrate the present invention and is a well known signaling protocol utilized in the art of telephony telecommunication, the instant invention is not limited to the use of signaling system 7 (SS7) signaling for call establishment of an off-network call; the use of signaling system 7 (SS7) signaling is merely illustrative. As such, other methods of signaling may be substituted for signaling system 7 (SS7).
11. When the called public switched telephone network user terminates the link, an on hook signal may be sent to

27

the appropriate public switched telephone network switch, such as a 5ESS. The signaling network may then send a call termination message (not shown) to the signaling gateway 234 as notification of the call termination status.

12. The signaling gateway 234 may then generate a release 524 signal to the call manager 218.
13. Upon receipt of the release 524 signal, the call manager 218 may a) initiate the relinquishment of the provisioned network resources by issuing a close connection 525 message to the voice gateway (VG) 232 and a release complete 526 message to the signaling gateway 234, b) inform the accounting gateway that the call has been terminated, for billing purposes via, for example, sending a call end 527 message to the accounting gateway 240.
14. With reference to the close connection 525 message, the voice gateway may respond by issuing a report message 528 to the call manager 218 containing the current status of the call.
15. On receiving the call status report 528, the call manager 218 may issue a delete connection 529 message to the broadband residential gateway 300.
16. The broadband residential gateway 300 may then releases its resources and sends a status report 530 to the call manager 218. In addition to the report 530, the broadband residential gateway 300 may also send an on hook 531 status report to the call manager 218.
17. The call manager 218 may then inform the broadband residential gateway 300 to report the next off hook condition via message 532.
18. Where a cable modem transmission system is utilized, the call manager 218 may then issues a release gate 533 message to the cable modem transmission system 116 so that all the modem resources can be relinquished. Once the gate resources have been released, the cable modem transmission system 118 sends a release gate complete 534 message to the call manager 218. At this point, all resources pertaining to the call have been relinquished.

C. Exemplary Call Flow of an On-Network Call to another On-Network User, Under One Call Manager Control

FIG. 6 illustrates an exemplary call flow of an on-network call to another on-network user, with the call being handled by a single call manager (CM) 218. In alternate embodiments, different portions of the call set-up sequence may be handled by more than one call manager 218 in the IP network 120. The exemplary "on-network" call processing sequence operates as follows:

1. Once the broadband residential gateway 300A detects and off hook condition of, for example, a telephone, the broadband residential gateway 300A may generate an off hook signal 607 to the call manager (CM) 218. The off hook signal may act as a dial tone request to the call manager 218.
2. The call manager 218 may then issue a dial tone message 608 to the requesting near-side broadband residential gateway 300A in order for the broadband residential gateway 300A to generate a dial tone.
3. The call manager 218 may then enter a state where it polls and collects the dialed digits 609 from broadband residential gateway 300A. The dialed digits are transferred to the call manager 218 one at a time. In a similar fashion to the subject matter discussed above, in embodiments where the call setup is shared between the call manager 218 and the broadband residential gateway 300A, the broadband residential gateway may manage

28

the call set-up and transfer both the off-hook signal and the dialed digits to the call manager 218 within one or more.

4. On receiving the completed dialed digits, the call manager 218 may issue a local number portability query 610 to the IP local number portability database 122. The IP local number portability database 122 may then supply the call manager 218 with a routing number 611 if the dialed digits constitute a valid sequence.
5. The call manager 218 may then ensure that adequate network resources are available to accommodate the call.
6. Where adequate resources are available, the call manager 218 may issue a first setup message 612 to whatever mechanism couples the far side broadband residential gateway 300, e.g., the cable modem transmission system 116B, to allocate transmission resources on the far side.
7. A call proceeding message and a report on hook condition message 613 may then be sent to the broadband residential gateway 300A.
8. A gate allocation message 614 may then be sent from the call manager 218 to the cable modem transmission system 116A, where the broadband residential gateway 300A is coupled via a cable modem transmission system. In this environment, a gate allocation 614 message may be utilized to set up the relevant modem resources.
9. Where a cable modem transmission system is utilized and receives the setup message 612 from call manager 218, the cable modem transmission system 116B may then send a connection request 615 message to the far side broadband residential gateway 300B.
10. Where a cable modem transmission system 116B is utilized, the cable modem transmission system may then sends a setup acknowledgement 616 to call manager 218. Once the resources are allocated by the cable modem transmission system 116A, the cable modem transmission system may then send a gate allocation acknowledgement message 617 back to the call manager 218.
11. Once the call manager 218 receives the setup acknowledgement 616 along with the gate allocation acknowledgement message 617, the far-side broadband residential gateway 300B may then send a ringing message 618 to the far-side cable modem transmission system 116B where this connectivity is utilized.
12. In these embodiments, the far-side cable modem transmission system 116B may then issue an alerting message 619 to the call manager 218.
13. The call manager 218 may then convey the alert via an alerting message 620 to the broadband residential gateway 300A, to produce an indicating signal such as a ringing signal indicating that the call is going through.
14. The cable modem transmission system 116B may then issue a connect message 622 to the call manager 218 in response to the far-side broadband residential gateway 300B sending an off hook message 621 to the far-side cable modem transmission system 116B. At this point, the end-to-end communication path is established and conversation 623 can be facilitated.
15. Assuming that the calling party hangs up first, the broadband residential gateway 300A may initiate an on hook sequence 624 message which may be communicated to the near-side cable modem transmission system 116A.
16. The cable modem transmission system 116A may then issue a disconnect message 625 to the call manager (CM) 218. The call manager 218 may then issue a first

29

delete connection request **626** to the near-side broadband residential gateway **300A** and then a second delete connection request **627** to the far-side broadband residential gateway **300B**.

17. The near-side broadband residential gateway **300A** may respond to the call manager **218** with a report message **628** containing the connection status, as well as an on hook message **630** to verify that the calling party at near-side broadband residential gateway **300A** has terminated the call.
18. The far-side broadband residential gateway **300B** may respond to the call manager **218** with a report message **629** containing the connection status, as well as an on hook message **631** indicating that the called party connection has now been terminated.
19. At this point, the call manager **218** may issue release gate messages **634** and **635** to the near-side cable modem transmission system **218** and far side cable modem transmission system **116B**, respectively, so as to release the modems associated with the call. Once all the resources have releases, the cable modem transmission system **116A** and the cable modem transmission system **116B** may issue gate release complete messages **636** and **637** respectively to the call manager **218**.
20. For simplicity, the accounting processing is not shown. However, the process used in FIG. **5** may be utilized as the billing procedure for on-net calls. Such a process might constitute sending a call start message from the call manager **218** to an accounting gateway (AG) **240** after the connect message **622** is sent from the far-side cable modem transmission system **116B** to call manager **218**. The call start message would trigger the start of the billing procedure. A corresponding call end message would then be sent from the call manager **218** to the AG **240** after the near-side cable modem transmission system **116A** sends a the disconnect message **625** to the call manager **218**. This call end message would trigger the ending of the billing procedure for that call.

Although the IP voice packets for these calls are typically routed over the IP network **120**, the system may, where appropriate, route IP voice packets over the Internet **180**.

II. BRG Greeting and Message Features and Multiple Line Configurations

The BRG can be configured to satisfy individual customer needs. The BRG may be configured to provide multiple telephone lines using a single DN. Also, the BRG may be configured so that it is associated with multiple DNs. The single DN configuration allows for multiple active telephone lines without increasing the number of DNs required. Thus, the demand for additional DNs and the redistribution of DN area codes can be reduced. Furthermore, the telephone utility may charge a customer for every DN allocated to the customer. Thus, the single DN configuration is a cost effective alternative to using multiple DNs for multiple telephone lines.

A first preferred embodiment utilizing the single DN configuration will be described in conjunction with FIG. **7**. FIG. **7** shows four telephony ports **332**, however, BRG **300** may be configured to include more or less than four telephony ports. The telephony port(s) may be configured, so existing user POTS telephones **110** connect directly to BRG **300** through RJ-11 connectors without modification. Additionally, the BRG may be configured, so digital ISDN telephones and IP telephones can be connected to ports on the BRG. Each port may connect to one or more POTS telephones. Multiple POTS telephone units can connect to a telephony port on the BRG with a conventional two-wire loop.

30

Incoming voice packets include a DN and an IP address. Each telephony port on the BRG is associated with a distinct IP address. IP addresses for each active BRG port are mapped to a single DN by the network for packet routing purposes. Mapping of IP addresses is created and administered by the CM. The CM maintains, in a database or table, mappings between directory numbers and IP addresses. When an incoming call directed to a particular DN is received by the CM, the CM will query the database or table for the associated IP address. The CM will attempt to route the incoming call to the associated IP address.

FIG. **8** shows a flow chart of the first preferred embodiment. In step **400**, the CM maps a directory number with the IP addresses of multiple ports on the BRG. In step **401**, an incoming call (IP voice packet) with the directory number of BRG **300** arrives at BRG **300**, shown as **1** in FIG. **7**. In step **402**, BRG **300** is programmed to route all packets attempting to establish a voice connection to a port connected to personal computer (PC) **333** (e.g. port **4**), shown as **2** in FIG. **7**. A PC-based sound card or telephony card **334** is connected to PC **333**. Port **4** rings PC **333**, shown as **3** in FIG. **7**, and sound card **334** answers the call by playing a greeting in step **403**. For example, the caller may be greeted with a salutation, which may be computer generated or pre-recorded, followed by a menu of parties or extensions which can be reached via the BRG (e.g. "to reach Mr. . . . , press or say **1**"). In step **404**, the caller selects the party or extension attempting to be reached. Once a particular party or extension is selected, PC **333** determines which port is connected to the telephone used by the selected party or extension, shown as **4** in FIG. **7**. To determine which port has been selected, PC **333** includes software for associating each party or extension with a telephony port **332** connected to a telephone used by that party or extension. Additionally, a message, discussed below, may optionally be played after the party is selected. In step **405**, PC **333** then instructs BRG **300**, through the Ethernet connection shown as **5**, to direct the incoming call to the port connected to the telephone associated with the party or extension the caller is attempting to reach. IP packets are then routed, shown as **6** in FIG. **7**, to the respective port (in this case port **1**). In step **406**, the telephone(s) connected to the selected port may distinctively ring, and BRG **300** may display and announce the identity of the selected port as described below.

BRG **300** may be configured to distinctively ring telephone **110** connected to a port on BRG **300**, so the telephones may be distinguished by sound. For example, telephone **110** connected to port **1** will ring differently than a telephone connected to ports **2** or **3** on BRG **300**. PC **333** is programmable to instruct BRG **300** to provide a distinctive ring associated with one or more of the parties or extensions. BRG **300** may be used to provide distinctive ringing by controlling the timing of the voltage applied to the port which causes telephone **110** to ring. Alternatively, a digital telephone or a programmable IP telephone connected to a port on BRG **300** may be programmed to provide a distinctive ring, or PC **333** may send a signal instructing the telephone to ring distinctively. Also, if multiple digital or programmable IP telephones are connected to a single port, BRG **300** may be programmed to address each phone individually to instruct each to ring distinctively.

Also, to provide a user friendly method for reaching a particular person, each telephony port may have a unique identity, such as a name, number, or tone, which can be combined with the BRG greeting feature. For example, the BRG display **338** may indicate the name or extension of the selected party or extension. Also, the BRG may provide a computer generated announcement of the name or extension

31

of the party selected by the caller using the external/internal Intercom Module (IM) **344**. Also, the BRG may play a tone which is associated with the selected party or extension.

Additionally, BRG **300** may include a message feature. PC **333** can be programmed to play a message associated with the party or extension selected by the caller. The message, for example, may instruct the caller to leave a message for the party attempting to be reached or indicate the caller is unavailable.

The greeting and message provided by PC **333** may be customized by recording from a digital phone, from a microphone attached to sound card **334** in PC **333**, or from a built in microphone in BRG **300**. Additionally PC **333** may store multiple greetings and messages, and PC **333** may be programmed to selectively use several greetings and messages. The user can program PC **333** to use a particular greeting or message at particular times or use a particular greeting or message for incoming calls originating from particular DNs or IP addresses. Furthermore, BRG **300** is not limited to providing greeting, message and routing functions through PC **333**. All functions performed by PC **333** may be provided using only BRG **300**. The BRG operating program store **330** may include instructions for performing all the functions of PC **333**.

FIG. 9 shows a flow chart of a second preferred embodiment. The block diagram shown in FIG. 7 will also be used to describe the second embodiment. In the second preferred embodiment, BRG **300** is identified by multiple DNs. In step **500**, IP addresses for each active BRG port are mapped to the multiple DNs by the CM for packet routing purposes. This embodiment may be advantageous, for example, when a user needs a private number and business number allocated to the same premises. An incoming call with a DN mapped to an IP address associated with the BRG is received in step **501**. In this embodiment, BRG **300** directs an incoming call similarly to the first embodiment. In step **502**, an incoming call is directed to a port connected to PC **333** (e.g. port **4**). In step **503**, PC **333** provides a greeting which may prompt the caller to select a party or extension. The caller selects a port associated with the party or extension in step **504**. After selecting the port, a message pertaining to the party or extension may optionally be played. PC **333** then directs the incoming call to the port connected to the telephone associated with the selected party or extension (e.g. port **1**) in step **505**. In step **506**, the telephone(s) connected to the port will provide an alert to the incoming call. The alert may be a distinctive ring. Also, the BRG may display or announce the identity of the selected port. In this preferred embodiment, BRG **300** will direct incoming calls with any of the multiple DNs associated with the BRG to the port connected to the PC **333**. In addition, PC **333** may be programmed to automatically associate a particular port with a particular DN. Thus, the incoming call may be automatically routed to a port associated with the DN without requiring the caller to make a selection, as shown in step **507**. Also, the second preferred embodiment may use the greeting and messaging features described in the first preferred embodiment, and all functions performed by PC **333** may be provided using only BRG **300**.

What has been described are the preferred embodiments of the present invention. However, it will be readily apparent to those skilled in the art that it is possible to embody the invention in specific forms other than those disclosed in the preferred embodiments described above. This may be done without departing from the spirit of the invention, and the preferred embodiments are merely illustrative and should not

32

be considered restrictive in any way. The scope of the invention is given by the appended claims, rather than the preceding description.

The following U.S. patent applications, which are related to the present application, are hereby incorporated by reference:

U.S. patent application Ser. No. 09/475,167 entitled "Automatic Port Status Reporting and Selective Call Barge-in For a Broadband Voice Over IP Telephony System and Method" invented by Kung et al.

U.S. patent application Ser. No. 09/475,140 entitled "Automatic Cable Phone Service Activation," invented by Kung et al.

U.S. patent application Ser. No. 09/475,141, entitled "Broadband Cable Telephony Network Architecture IP ITN Network Architecture Reference Model," invented by Kung et al.

U.S. patent application Ser. No. 09/475,142, entitled "IP Conference Call Waiting" invented by Kung et al.

U.S. patent application Ser. No. 09/475,143, entitled "Conference Server for Automatic X-Way Call Port Expansion Feature", invented by Kung et al.

U.S. patent application Ser. No. 09/475,197, entitled "Wireless Touch Screen Television," invented by Kung et al.

U.S. patent application Ser. No. 09/475,195, entitled "Programmable Feature Buttons on a Broadband Residential Gateway," invented by Kung et al.

U.S. patent application Ser. No. 09/475,745, entitled "Automatic Call Manager Traffic Gate Feature," invented by Kung et al.

U.S. patent application Ser. No. 09/475,201, entitled "Local Number Portability Database for On-net IP Call," invented by Kung et al.

U.S. patent application Ser. No. 09/475,747, entitled "Personal IP Follow Me Service," invented by Kung et al.

U.S. patent application Ser. No. 09/475,194, entitled "Personal IP Toll-Free Number," invented by Kung et al.

U.S. patent application Ser. No. 09/475,196, entitled "User Programmable Port Hunting in an IP Based Customer Premise Equipment," invented by Kung et al.

U.S. patent application Ser. No. 09/475,146, entitled "IP Leased Line," invented by Kung et al.

U.S. patent application Ser. No. 09/475,160, entitled "Anonymous Call Rejection," invented by Kung et al.

U.S. patent application Ser. No. 09/475,161, entitled "Automatic Callback With Distinctive Ringing," invented by Kung et al.

U.S. patent application Ser. No. 09/475,162, entitled "IP Multimedia Call Blocking," invented by Kung et al.

U.S. patent application Ser. No. 09/475,144, entitled "IP Call Forward Profile," invented by Kung et al.

U.S. patent application Ser. No. 09/475,671, entitled "IP Call Forward Follow Me," invented by Kung et al.

U.S. patent application Ser. No. 09/475,670, entitled "Enhanced BRG with Display Capabilities," invented by Kung et al.

U.S. patent application Ser. No. 09/475,672, entitled "Hand Held Integrated IP Device," invented by Kung et al.

U.S. patent application Ser. No. 09/472,292, entitled "Wireless Settop Box," invented by Kung et al.

U.S. patent application Ser. No. 09/475,145, entitled "BRG PCMCIA Card Cable Ready for PCs," invented by Kung et al.

U.S. patent application Ser. No. 09/476,494, entitled "Broadband Service Access," invented by Kung et al.

U.S. patent application Ser. No. 09/475,798, entitled "Method for Providing Broadband Public IP Services," invented by Kung et al.

U.S. patent application Ser. No. 09/475,797, entitled "Method For Billing IP Broadband Subscribers," 5 invented by Kung et al.

U.S. patent application Ser. No. 09/475,165, entitled "BRG With PBX Capabilities," invented by Kung et al.

U.S. patent application Ser. No. 09/475,783, entitled "Enhanced IP Subscriber Alerting," invented by Kung et al. 10

U.S. patent application Ser. No. 09/475,782, entitled "Chase Me System," invented by Kung et al.

U.S. patent application Ser. No. 09/475,673, entitled "Call Hold With Reminder and Information Push," invented by Kung et al. 15

U.S. patent application Ser. No. 09/475,293, entitled "Activity Log For Improved Call Efficiency," invented by Kung et al. 20

U.S. patent application Ser. No. 09/475,779, entitled "Selective Information Admission," invented by Kung et al.

U.S. patent application Ser. No. 09/475,166, entitled "User Programmable Fail-proof IP Hotline/Warm-line," 25 invented by Kung et al.

U.S. patent application Ser. No. 09/476,493, entitled "Authentication of Broadband IP Telephony Service," invented by Kung et al.

U.S. patent application Ser. No. 09/475,667, entitled "Simplified IP Service Control," invented by Kung et al. 30

U.S. patent application Ser. No. 09/475,661, entitled "Protected IP Telephony Calls Using Encryption (P.I.E.—Protected IP Encryption)," invented by Kung et al. 35

U.S. patent application Ser. No. 09/475,294, entitled "Integrated Multimedia Messaging Service," invented by Kung et al.

U.S. patent application Ser. No. 09/475,666, entitled "Remote Monitoring Through the BRG," invented by Kung et al. 40

U.S. patent application Ser. No. 09/475,296, entitled "Cable Headend System with Pseudo-Switching Capabilities," invented by Kung et al.

U.S. patent application Ser. No. 09/475,287, entitled "A Method for Performing Roaming Across Multiple IP networks," invented by Kung et al. 45

U.S. patent application Ser. No. 09/475,662, entitled "Scalable VoIP network Server For Low Cost PBX," invented by Kung et al. 50

U.S. patent application Ser. No. 09/475,288, entitled "Call Services Transfer," invented by Kung et al.

U.S. patent application Ser. No. 09/475,204, entitled "Multiple Call Waiting in a Packetized Communication System," invented by Kung et al. 55

U.S. patent application Ser. No. 09/475,205, entitled "Optimizing Voice Paths in an IP Telephony Network," invented by Kung et al.

U.S. patent application Ser. No. 09/475,203, entitled "Call Waiting and Forwarding in a Packetized Communication System," invented by Kung et al. 60

U.S. patent application Ser. No. 09/475,202, entitled "Incoming Call Identification in IP Telephony," invented by Kung et al.

U.S. patent application Ser. No. 09/475,290, entitled "Incoming IP Call Remote Party Data," invented by Kung et al. 65

U.S. patent application Ser. No. 09/475,295, entitled "Personal User Network (Closed User Network) PUN, CUN," invented by Kung et al.

U.S. patent application Ser. No. 09/475,668, entitled "IP Address Interworking Unit (IAIU) For Automatic IP V4 to V6 Address Translation," invented by Kung et al.

U.S. patent application Ser. No. 09/475,669, entitled "Automatic Off-Hook Recovery and Fail-Proof Call Delivery," invented by Kung et al.

The invention claimed is:

1. A single physical device comprising:

a plurality of integrated communications interfaces to multiple other devices at a customer premise, wherein the plurality of integrated communications interfaces comprise a telephone port connection and an Ethernet connection, and wherein the multiple other devices comprise a plain old telephone system (POTS) phone and an Internet Protocol (IP) phone;

a transceiver comprising a register to facilitate data transfer across an IP network;

a processing unit coupled to a memory, wherein the memory comprises instructions to respond to receipt of an incoming call comprising an IP packet via the transceiver, with a greeting that includes a prompt, and to route the incoming call from the IP network to the IP phone of a party or an extension selected from among the multiple other devices by a caller in response to the prompt.

2. The single physical device of claim 1 further comprising: a CODEC configured to convert an analog voice signal into IP packets.

3. The single physical device of claim 1 further comprising: an intercom module to provide an announcement of at least a name of the party or the extension selected by the caller.

4. The single physical device of claim 1 further comprising: an intercom module to set-up an intercom connection to another device.

5. The single physical device of claim 1 wherein: multiple IP phones are connected to a single port.

6. The single physical device of claim 5 being programmed to address each IP phone individually.

7. The single physical device of claim 1 further comprising: circuitry configured to detect unused telephone(s) and generate a special intercom tone on the unused telephone(s).

8. The single physical device of claim 1 wherein: the greeting is based on at least a telephone directory number (DN) or an IP address from which the incoming call originates.

9. The single physical device of claim 1 further comprising a message feature to play a message associated with the party or the extension selected by the caller.

10. A method of operating at least a single physical device, the method comprising:

responding to an incoming call comprising an Internet Protocol (IP) packet with a greeting that includes a prompt;

wherein the IP packet is received via a transceiver in the single physical device, the transceiver comprising a register to facilitate data transfer across an IP network from which the incoming call is received, the single physical device further comprising a plurality of integrated communications interfaces to multiple other devices at a customer premise, the plurality of integrated communications interfaces comprising a telephone port connection and an Ethernet connection, the multiple other

35

devices comprising a plain old telephone system (POTS) phone and an IP phone; and
 routing the incoming call from the IP network to the IP phone of a party or an extension selected from among the multiple other devices by a caller in response to the prompt. 5

11. The method of claim **10** further comprising:
 converting an analog voice signal into IP packets.

12. The method of claim **10** further comprising:
 providing an announcement of at least a name of the party or the extension selected by the caller. 10

13. The method of claim **10** further comprising:
 providing an intercom connection to another device at a remote location.

14. The method of claim **10** wherein:
 multiple IP phones are connected to a single port. 15

15. The method of claim **14** further comprising:
 addressing each IP phone individually.

16. The method of claim **10** further comprising:
 detecting unused telephone(s); and
 generating a special intercom tone on the unused telephone(s). 20

36

17. The method of claim **10** wherein:
 the greeting is based on at least a DN or IP address from which the incoming call originates.

18. The method of claim **10** further comprising:
 providing a message after the greeting, the message being associated with a name of the party or the extension selected by the caller.

19. The method of claim **10** wherein:
 said single physical device is hereinafter a first single physical device;

the incoming call originates in a second single physical device; and

the method further comprises establishing an end-to-end communication path between the second single physical device and the first single physical device.

20. The method of claim **10** wherein:
 multiple IP phones are coupled to the single physical device; and

the method further comprises instructing each IP phone to ring distinctively.

* * * * *